SIEMENS

Data sheet US2:52PP2K5XB

30mm Command/52, Chrome Finish Heavy Duty, Watertight/Oiltight Complete Metal Unit Illuminated Push-Pull Operator Transformer type, 600V AC LED Lamp Mushroom Head Cap Small 1 3/4" (44.5 mm) Metal, Chrome with Blue Lens 2 Position Maintained, Pull-to-Release UL Listed, CSA Certified NEMA 1,3,3R,4,4X,12,13 & Automotive Standards

	1,3,3R,4,4X,12,13 & Automotive Standards
design of the product	Actuator round
Enclosure	
number of command points	1
delivery state as a kit	No
Actuator	
product extension optional light source	Yes
material of the actuating element	metal mushroom head with plastic lens
type of unlocking device	pull-to-unlatch mechanism
number of switching positions	2
Front ring	
product component front ring	Yes
design of the front ring	standard
material of the front ring	metal
color of the front ring	chrome
Holder	
material of the holder	Metal
Contact block/ lampholder	
socket design	BA 9s with LED
number of lampholders	1
Display	
number of LED modules	1
General technical data	
product component	
lamp transformer	Yes
• light source	Yes
degree of pollution	1
type of voltage	·
of the operating voltage	AC
of the input voltage	AC
surge voltage resistance rated value	4 kV
protection class IP	IP66
of the terminal	IP20
Supply voltage	11 20
	AC
type of voltage of the supply voltage of the light source supply voltage of the light source at AC at 60 Hz	AU
rated value	6 V
• rated value Inputs/ Outputs	6 V
	6.7/
output voltage 1 of the lamp transformer rated value	6 V
Connections/ Terminals	construction of the state of th
type of electrical connection	screw-type terminals
 of modules and accessories 	•
Alabaanian tanana af the enemia in the 1	Screw-type terminal
tightening torque of the screws in the bracket	Screw-type terminal 20 N·m
tightening torque [lbf·in] with screw-type terminals	Screw-type terminal
tightening torque [lbf-in] with screw-type terminals	Screw-type terminal 20 N·m 8 8 lbf·in
tightening torque [lbf-in] with screw-type terminals Lamp type of light source	Screw-type terminal 20 N·m 8 8 lbf·in LED
tightening torque [lbf·in] with screw-type terminals Lamp type of light source color of the light source	Screw-type terminal 20 N·m 8 8 lbf·in
tightening torque [lbf-in] with screw-type terminals Lamp type of light source	Screw-type terminal 20 N·m 8 8 lbf·in LED

Ambient conditions	
ambient temperature	
 during operation 	-35 +70 °C
 during storage 	-40 +85 °C
Installation/ mounting/ dimensions	
shape of the installation opening	round
Certificates/ approvals	
= 0 : t c	

Siemens has decided to exit the Russian market (see here).

https://press.siemens.com/global/en/pressrelease/siemens-wind-down-russian-business

Siemens is working on the renewal of the current EAC certificates.

Please contact your local Siemens office on the status of validity of the EAC certification if you intend to import or offer to supply these products to an EAC relevant market (other than the sanctioned EAEU member states Russia or Belarus).

Information on the packaging

https://support.industry.siemens.com/cs/ww/en/view/109813875

Information- and Downloadcenter (Catalogs, Brochures,...)

https://www.siemens.com/ic10

Industry Mall (Online ordering system)

https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=US2:52PP2K5XB

Cax online generator

http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=US2:52PP2K5XB

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

https://support.industry.siemens.com/cs/ww/en/ps/US2:52PP2K5XB

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...) http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=US2:52PP2K5XB&lang=en

last modified: 5/31/2021 🖸