## **SIEMENS**

## Data sheet

## US2:52PP3JR

	30mm Command/52, Chrome Finish Heavy Duty,Watertight/Oiltight Complete Metal Unit Illuminated Push-Pull Operator Transformer type, 480V AC Incandescent Lamp Mushroom Head Cap Small 1 3/4" (44.5 mm) Plastic, Red 3 Position Momentary UL Listed, CSA Certified NEMA 1,3,3R,4,4X,12,13 & Automotive Standards
design of the product	Actuator round
Enclosure	
number of command points	1
delivery state as a kit	No
Actuator	
product extension optional light source	Yes
material of the actuating element	plastic
type of unlocking device	without
number of switching positions	3
Front ring	
product component front ring	Yes
design of the front ring	standard
material of the front ring	metal
color of the front ring	chrome
Holder	
material of the holder	Motol
Contact block/ lampholder	Metal
socket design	BA 9s with lamp
number of lampholders	1
Display	
number of LED modules	0
General technical data	
product component	
<ul> <li>lamp transformer</li> </ul>	Yes
light source	Yes
degree of pollution	1
type of voltage	
<ul> <li>of the operating voltage</li> </ul>	AC
<ul> <li>of the input voltage</li> </ul>	AC
surge voltage resistance rated value	4 kV
protection class IP	IP66
<ul> <li>of the terminal</li> </ul>	IP20
Supply voltage	
type of voltage of the supply voltage of the light source	AC
supply voltage of the light source at AC at 60 Hz	
• rated value	6 V
Inputs/ Outputs	
output voltage 1 of the lamp transformer rated value	6 V
Connections/ Terminals	
	serow type terminale
type of electrical connection • of modules and accessories	screw-type terminals Screw-type terminal
	20 N·m
tightening torque of the screws in the bracket	
tightening torque [lbf·in] with screw-type terminals	8 8 lbf-in
Lamp	
type of light source	filament lamp
color of the light source	clear
Safety related data	
touch protection against electrical shock	finger-safe

Subject to change without notice © Copyright Siemens

Ambient conditions		
ambient temperature		
during operation	-35 +70 °C	
during storage	-40 +85 °C	
Installation/ mounting/ dimensions		
shape of the installation opening	round	
Certificates/ approvals		
Further information		
https://press.siemens.com/global/en/pressrelease/siemens-wind-do Siemens is working on the renewal of the current EAC certifica Please contact your local Siemens office on the status of validity of EAC relevant market (other than the sanctioned EAEU member stat Information on the packaging https://support.industry.siemens.com/cs/ww/en/view/109813875 Information- and Downloadcenter (Catalogs, Brochures,) https://www.siemens.com/ic10 Industry Mall (Online ordering system) https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb= Cax online generator http://support.automation.siemens.com/WW/CAXorder/default.aspx Service&Support (Manuals, Certificates, Characteristics, FAQs https://support.industry.siemens.com/cs/ww/en/ps/US2:52PP3JR Image database (product images, 2D dimension drawings, 3D r http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=US2	tes. the EAC certification if you intend to import or offer to supply these products to an tes Russia or Belarus). =US2:52PP3JR ?lang=en&mlfb=US2:52PP3JR ,) models, device circuit diagrams, EPLAN macros,)	

```
last modified:
```

5/31/2021 🖸