## SIEMENS

## Data sheet

## US2:52PP3K2U

30mm Command/52, Chrome Finish Heavy Duty,Watertight/Oiltight Complete Metal Unit Illuminated Push-Pull Operator Transformer type, 600V AC Incandescent Lamp Mushroom Head Cap Small 1 3/4" (44.5 mm) Metal, Chrome with Red Lens 3 Position Momentary 1 N.C.+1 N.C. Extra Late Break Heavy Duty Contacts, A600/P600 UL Listed, CSA Certified NEMA 1,3,3R,4,4X,12,13 & Automotive Standards



Enclosure		
number of command points	1	
delivery state as a kit	No	
Actuator		
product extension optional light source	Yes	
number of contact modules	2	
type of unlocking device	without	
number of switching positions	3	
Front ring		
product component front ring	Yes	
design of the front ring	standard	
material of the front ring	metal	
Contact block/ lampholder		
number of lampholders	1	
Display		
number of LED modules	0	
General technical data		
product function positive opening	No	
product component		
lamp transformer	Yes	
light source	Yes	
insulation voltage rated value	600 V	
type of voltage		
<ul> <li>of the operating voltage</li> </ul>	AC	
<ul> <li>of the input voltage</li> </ul>	AC	
surge voltage resistance rated value	4 kV	
protection class IP	IP66	
• of the terminal	IP20	
thermal current	10 A	
Supply voltage		
type of voltage of the supply voltage of the light source	AC	
supply voltage of the light source at AC at 60 Hz		
rated value	6 V	
Auxiliary circuit		
number of NC contacts for auxiliary contacts	2	
number of NO contacts for auxiliary contacts	0	
operational current at AC-15		
• at 110 V rated value	60 A	
• at 230 V rated value	30 A	
• at 400 V rated value	15 A	

• at 500 V rated value	12 A	
Inputs/ Outputs		
output voltage 1 of the lamp transformer rated value	6 V	
Connections/ Terminals		
type of electrical connection	screw-type terminals	
tightening torque of the screws in the bracket	20 N·m	
tightening torque [lbf·in] with screw-type terminals	8 8 lbf·in	
Lamp		
color of the light source	clear	
Ambient conditions		
ambient temperature		
during operation	-35 +70 °C	
during storage	-40 +85 °C	
Installation/ mounting/ dimensions		
shape of the installation opening	round	
Certificates/ approvals		
Further information		
Siemens has decided to exit the Russian market (see here).		
https://press.siemens.com/global/en/pressrelease/siemens-wind-down-russian-business		
Siemens is working on the renewal of the current EAC certificates.		
Please contact your local Siemens office on the status of validity of the EAC certification if you intend to import or offer to supply these products to an EAC relevant market (other than the sanctioned EAEU member states Russia or Belarus).		
Information on the packaging		
https://support.industry.siemens.com/cs/ww/en/view/109813875		
Information- and Downloadcenter (Catalogs, Brochures,)		
https://www.siemens.com/ic10		
Industry Mall (Online ordering system) https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=US2:52PP3K2U		
Cax online generator		
http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=US2:52PP3K2U		
Service&Support (Manuals, Certificates, Characteristics, FAQs,)		
https://support.industry.siemens.com/cs/ww/en/ps/US2:52PP3K2U		
Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros,)		
http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=US2:52PP3K2U⟨=en		

last modified:

5/31/2021 🖸