SIEMENS

Data sheet

US2:52PP3KBXB

30mm Command/52, Chrome Finish Heavy Duty,Watertight/Oiltight Complete Metal Unit Illuminated Push-Pull Operator Transformer type, 600V AC LED Lamp Mushroom Head Cap Small 1 3/4" (44.5 mm) Metal, Chrome with White Lens 3 Position Momentary UL Listed, CSA Certified NEMA 1,3,3R,4,4X,12,13 & Automotive Standards

design of the product Actuator round Enclosure I Enclosure No Actuator No Actuator Yes color of the actuating dement white matcrial of the actuating dement white matcrial of the actuating dement white number of whiching positions 3 Front ring Yes odding of the front ring abudard design of the front ring metal color of the front ring metal color of the front ring desid color of the front ring Metal color of the front ring Kes socki design Metal color of the front ring Kes color of th		Automotive Standards
number of command points 1 delivery state as a kit No Actuator Product advansion optional light source Yes product advansion optional light source Yes color of the actualing element metal mushroom head with plastic lens type of unlocking double without number of switching positions 3 Product component front ring standard design of the front ring standard color of the front ring chrome Adding metal color of the front ring chrome Metal Context block/ light source Ves design of the front ring color of the front ring metal socket design Bd Re with LED number of LED modules 1 Display Tomeson number of LED modules 1 ot the operating voltage AC	design of the product	Actuator round
delivery state as a kit No Actuator Ves oclor of the actuating element while material of the actuating element metal mushroom head with plastic lens type of unicoting dovico without mumber of switching positions 3 Front ring Ves design of the front ring standard material of the holder Metal color of the front ring chrome actuator metal color of the front ring chrome material of the holder Metal Contact block lampholders 1 color of the front ring BA 98 with LED number of LED modules 1 Contact block lampholders 1 orger of pollution 1 type of voltage Yes ilight source Yes of the operating voltage AC	Enclosure	
Actuator Ves product extension optional ignorement white material of the actuating element metal machroom head with plastic lens type of uniceking device without number of switching positions 3 Front ring Yes product component front ring Yes design of the front ring standard color of the front ring chrome Holds	number of command points	1
product extension optional light source Yes color of the actuating element white material of the actuating element metal mushroom head with plastic lens masterial of the actuating element metal mushroom head with plastic lens mumber of switching positions 3 Product component front ring Yes design of the front ring metal material of the holder Metal color of the front ring metal color of the front ring Metal Contact block/ lampholder Socket design socket design BA 9s with LED number of LED modules 1 Orderat block/ lampholder Socket design socket design AS 9s with LED number of LED modules 1 of the inplatasformer Yes elight source Yes elight source Yes elight source Yes elight source AC of the inplu voltage AC source voltage resistance rated value 4VV product component IP20	delivery state as a kit	No
color of the actuating element white material of the actuating element metal mushroom head with plastic lens type of unlocking device without number of switching positions 3 Front ring standard product component front ring Yes design of the front ring chorme color of the front ring chorme color of the noter design of the front ring color of the noter design of the front ring color of the noter design of the noter socket design AS 9s with LED number of LED modules 1 context biolox/tanpholer yes product component Yes elight source Yes degree of poliution 1 type of voltage AC of the input voltage	Actuator	
metarlal of the actualing element metal mushroom head with plastic lens type of unlocking device without number of switching positions 3 Front ring Yes design of the front ring standard color of the front ring of the front ring color of the front ring metal color of the front ring chrome Holder Metal Contract block/ lampholder chrome socket design DA Se with LED number of lampholders 1 Orderat block/ lampholders 1 General technical data of the oparting voltage Yes eight source Yes eight source Yes of the oparting voltage AC of the input voltage Head <	product extension optional light source	Yes
type of unlocking device without number of switching positions 3 Front ring standard product component front ring standard material of the front ring netelal color of the front ring chrome Holdar material of the front ring material of the holder Metal Contract block/lampholder socket design socket design B A 9s with LED number of LED modules 1 Orgenset block/lampholder socket design socket design Nage with LED number of LED modules 1 Orgenset technical data socket design of the portering wortage Yes of the sprating wortage AC of the input voltage AC of the input voltage AC of the input voltage AC of the input voltage of the light source at AC at 60 Hz strade value of the input voltage of the light source at AC at 60 Hz strade value of the terminal BV20 Supply voltage of the light source at AC	color of the actuating element	white
number of switching positions 3 Front ring From tring product component front ring standard material of the front ring metal color of the holder Metal Display Innumber of LED modules 1 number of LED modules 1 General tochnical data product component Yes Yes i along transformer Yes Yes of the operating youtage AC AC surge vortage AC AC of the input voitage AC Surgevortage resistance rated value of the terminal IP20 Supply voitage of the supply voitage of the light source of the terminal S V Connectional	material of the actuating element	metal mushroom head with plastic lens
Front ring Yes product component front ring skndard design of the front ring metal color of the front ring metal color of the front ring Metal Contact block/lampholder Metal contact block/lampholder BA 9s with LED number of lampholders 1 Origity 1 number of LED modules 1 General technical data Product component • lamp transformer Yes • lamp transformer Yes • lamp transformer Yes • of the operating voltage AC • of the operating voltage AC • of the input voltage AC • of the terminal IP20 Supply voltage of the supply voltage of the light source AC • rated value 6 V Inputs/ Outputs Sorew-type terminals • of of deterrial connection Sorew-type terminals • of ondules and accessories Sorew-type terminals • of ondules and accessories Sorew-type terminals	type of unlocking device	without
product component front ring Yes design of the front ring metal color of the front ring chrome Holder metal Control to the holder Metal Contact block/ fampholder Execution socket design BA 9s with LED number of LED modules 1 Objeky Impholder product component * • lamp transformer Yes • light source Yes • of the input votage AC • of the operating votage AC • of the operating votage AC • of the operating votage AC • of the input votage AC • of the operating votage AC • of the operating votage AC • of the operating votage of the light source AC • of the operating votage of the light source AC • of the terninal IP20 Supply votage of the light source at AC at 60 Hz • • of the light source at AC at 60 Hz • • of the light source at AC at 60 Hz	number of switching positions	3
design of the front ring standard material of the front ring metal color of the front ring chrome Holder Metal Contact block/ lampholder Socket design socket design SA 98 with LED number of lampholders 1 Display Incomponent of the front ring Yes of the foot socket design Yes of the operating voltage Yes of the operating voltage AC of the terminal IP20 Supply voltage AC of the terminal IP20 Supply voltage of the light source at AC at 60 Hz 6 V rated value 6 V totage of the light source at AC at 60 Hz 6 V	Front ring	
metal metal color of the front ring chrome hoter chrome material of the holder Metal Contact block/ lampholder socket design socket design BA 9s with LED number of lampholders 1 Socket design 1 General toch/includat 1 General toch/includat 1 General toch/includat Yes elamp transformer Yes elamp transformer Yes of the operating voltage AC of the operating voltage of the light source AC surge voltage resistance rated value AV protection class IP IP66 output voltage of the	product component front ring	Yes
color of the front ring chrome Holder Metal material of the holder Metal contract block/ lampholder E socket design BA 9s with LED number of lampholders 1 Display number of LED modules format lachnical data 1 general tachnical data Yes product component Yes i lamp transformer Yes of the operating voltage AC of the operating voltage of the light source AC of the terminal IP20 Supply voltage of the light source at AC at 60 Hz Vertage	design of the front ring	standard
Holder Metal Contact block/ lampholder EA 9s with LED number of lampholders 1 Display 1 number of LED modules 1 General technical data 1 product component Yes • lamp transformer Yes • light source Yes • of the operating votage AC • of the operating votage AC • of the operating votage AC • of the input votage AC • of the terminal IP20 votage of the light source at AC at 60 Hz IP20 • of the lamp transformer rated value AC surpe votage of the light source at AC at 60 Hz IP20 • of the lamp transformer rated value AC • of the lamp transformer rated value AC • of didue and accessories Screw-type terminal • of didue and accessories Screw-type terminal • of didue and accessories Screw-type terminal • of modules and accessories Screw-type terminal • of modules and accessories Screw-type terminal • of modules and accessories Screw-t	material of the front ring	metal
material of the holder Metal Contact block/ lampholder BA 9s with LED number of lampholders 1 Display 1 number of LED modules 1 General technical data 1 product component • • lamp transformer Yes • light source Yes • of the operating voltage AC • of the operating voltage AC • of the operating voltage AC • of the input voltage AC • of the terminal IP20 Supply voltage of the light source at AC at 60 H2 • • of the light source at AC at 60 H2 • • rated value 6 V Inputs/ Outgage 1 of the lamp transformer rated value 6 V • of modules and accessories Screw-type terminals • of of odides and access	color of the front ring	chrome
Contact block/ lampholder socket design BA 9s with LED number of lampholders 1 Display Interference number of LED modules 1 General technical data Interference product component Yes i lamp transformer Yes i lamp transformer Yes degree of pollution 1 type of voltage AC of the operating voltage AC of the operating voltage AC of the input voltage AC surge voltage resistance rated value 4 kV protection class IP IP66 of the light source at AC at 60 Hz IP20 supply voltage of the light source at AC at 60 Hz IP20 trated value 6 V hopts/ outputs IP20 output voltage 1 of the lamp transformer rated value 6 V hopts/ outputs IP20 output voltage 1 of the lamp transformer rated value 6 V hopts/ outputs IP20 output voltage 1 of the lamp transformer rated value	Holder	
socket design BA 9s with LED number of lampholders 1 Display 1 General technical data 1 General technical data 1 General technical data 1 Opticat component 1 • light source Yes degree of pollution 1 type of voltage 4C • of the operating voltage AC • of the input voltage AC • of the input voltage AC • of the input voltage AC • of the terminal IP20 Supply voltage of the light source AC • of the light source at AC at 60 Hz • value • rated value 6 V Inputs/ Outputs 6 V output voltage 1 of the light source at AC at 60 Hz • value • pot electrical connection 6 V Connections/ Terminals 6 V Connections/ Terminal 5 crew-type terminal tightening torque of the screws in the bracket 20 N·m tightening torque of the screws in the bracket 2	material of the holder	Metal
number of lampholders 1 Display I number of LED modules 1 General technical data General technical data product component Yes Ight source Yes degree of pollution 1 type of voltage AC of the operating voltage AC of the terminal IP20 Supply voltage of the terminal IP20 supply voltage of the light source AC output voltage of the light source AC supply voltage of the light source AC supply voltage of the light source at AC at 60 Hz Imput voltage of the light source output voltage 1 of the lamp transformer rated value 6 V Connections/ Terminals Screew-type terminals Screew-type terminals of modules and accessories </th <th>Contact block/ lampholder</th> <th></th>	Contact block/ lampholder	
Display 1 General technical data	socket design	BA 9s with LED
number of LED modules 1 General technical data	number of lampholders	1
General technical data product component • lamp transformer • lamp transformer • light source Yes degree of pollution 1 type of voltage • of the operating voltage • of the input voltage • of the input voltage • of the operating voltage of voltage • of the input voltage • of the terminal IP20 Supply voltage of the supply voltage of the light source • of voltage of the light source at AC at 60 Hz • rated value 6 V Inputs/ Outputs output voltage 1 of the lamp transformer rated value 6 V Connections/ Terminals Screw-type terminals • of modules and accessories Screw-type terminals • of modules and accessories Screw-type terminal • of modules and accessories Screw-type terminals • of modules and accessories Screw-type terminal • of modules and accessories Sl brin	Display	
product component Yes • lamp transformer Yes • light source Yes degree of pollution 1 type of voltage 1 • of the operating voltage AC • of the input voltage AC • of the input voltage AC • of the terminal IP66 • of the terminal IP20 Supply voltage AC • of the light source at AC at 60 Hz 6 V • light source at AC at 60 Hz 6 V • of a fle lamp transformer rated value 6 V Connections/ Terminals Screw-type terminals • of modules and accessories Screw-type terminals • of modules and accessories Screw-type terminal tightening torque of the sorce to the bracket 20 N·m tightening torque of the sorce with the bracket 20 N·m tightening torque of the sorce with the bracket 20 N·m	number of LED modules	1
Image from the series of the large random the bracketYesImage of pollution1type of voltageImage of the input voltageImage of the input voltageACSurge voltage resistance rated value4 kVImage of the terminalIP20Supply voltage of the light sourceACSupply voltage of the light source at AC at 60 HzImage of the light source at AC at 60 HzImage of the large transformer rated value6 VImage of the large transformer rated value6 VImage of electrical connectionScrew-type terminalsImage of electrical connectionScrew-type terminalsImage of the source of the branceScrew-type terminalsImage of the source of the source of the source of the sourceScrew-type terminalsImage of the sourceLEDImage of the light sourcewhite	General technical data	
• light sourceYesdegree of pollution1type of voltage-• of the operating voltageAC• of the input voltageAC• of the input voltage4 kVprotection class IPIP66• of the terminalIP20Supply voltageACsurge voltage of the supply voltage of the light sourceACsupply voltage of the light source at AC at 60 Hz-• rated value6 VInputs/ Outputs6 VConnections / TerminalsScrew-type terminalstype of electrical connectionScrew-type terminal• of modules and accessoriesScrew-type terminaltightening torque of the source the bracket20 N·mtightening torque of the sourceLEDtype of light sourceLEDtype of light sourcewhite	product component	
degree of pollution 1 type of voltage • of the operating voltage AC • of the input voltage AC • of the input voltage AC surge voltage resistance rated value 4 kV protection class IP IP66 • of the terminal IP20 Supply voltage supply voltage of the supply voltage of the light source AC supply voltage of the supply voltage of the light source AC supply voltage of the light source at AC at 60 Hz • rated value 6 V Inputs/ Outputs 6 V connections/ Terminals Screw-type terminals voltage and accessories Screw-type terminals • of modules and accessories Screw-type terminals • of modules and accessories Screw-type terminals • of modules and accessories Screw-type terminals tightening torque of the screws in the bracket 20 N-m tightening torque of the screws in the bracket 20 N-m tightening torque file/in) with screw-type terminals & lib/in Lamp LED white	 lamp transformer 	Yes
type of voltage AC • of the operating voltage AC • of the input voltage AC surge voltage resistance rated value 4 kV protection class IP IP66 • of the terminal IP20 Supply voltage KC supply voltage of the supply voltage of the light source AC supply voltage of the supply voltage of the light source at AC at 60 Hz • rated value • rated value 6 V output voltage 1 of the lamp transformer rated value 6 V Connections/ Terminals screw-type terminals • of modules and accessories Screw-type terminal tightening torque of the screws in the bracket 20 N·m tightening torque [libfin] with screw-type terminals 8 8 lbf-in Lamp LED type of light source LED color of the light source White	light source	Yes
• of the operating voltageAC• of the input voltageACsurge voltage resistance rated value4 kVprotection class IPIP66• of the terminalIP20Supply voltagetype of voltage of the supply voltage of the light sourceACsupply voltage of the supply voltage of the light sourceACsupply voltage of the light source at AC at 60 Hz6 V• rated value6 VInputs/ Outputs6 Voutput voltage 1 of the lamp transformer rated value6 Vconnections/ TerminalsScrew-type terminals• of modules and accessoriesScrew-type terminaltightening torque of the screws in the bracket20 N·mtightening torque (librin) with screw-type terminals8 8 librinLampLEDtype of light sourceLEDcolor of the light sourcewhite	degree of pollution	1
• of the input voltageACsurge voltage resistance rated value4 kVprotection class IPIP66• of the terminalIP20Supply voltageIP20supply voltage of the supply voltage of the light sourceACsupply voltage of the light source at AC at 60 Hz6 V• rated value6 VInputs/ Outputs6 Voutput voltage 1 of the lamp transformer rated value6 VConnections/ TerminalsScrew-type terminals• of modules and accessoriesScrew-type terminals• of modules and accessoriesScrew-type terminaltightening torque of the screws in the bracket20 N·mtightening torque [lbf-in] with screw-type terminals8 8 lbf-inLampLEDtype of light sourceLEDcolor of the light sourcewhite	type of voltage	
surge voltage resistance rated value 4 kV protection class IP IP66 • of the terminal IP20 Supply voltage IP20 supply voltage of the supply voltage of the light source AC supply voltage of the light source at AC at 60 Hz • rated value • rated value 6 V Inputs/ Outputs • of the lamp transformer rated value output voltage 1 of the lamp transformer rated value 6 V Connections/ Terminals screw-type terminals type of electrical connection screw-type terminals • of modules and accessories Screw-type terminals tightening torque of the screws in the bracket 20 N·m tightening torque [lbf-in] with screw-type terminals 8 8 lbf-in Lamp LED type of light source LED color of the light source white	 of the operating voltage 	AC
protection class IP IP66 • of the terminal IP20 Supply voltage IP20 type of voltage of the supply voltage of the light source AC supply voltage of the supply voltage of the light source at AC at 60 Hz 6 V • rated value 6 V Inputs/ Outputs 6 V output voltage 1 of the lamp transformer rated value 6 V Connections/ Terminals screw-type terminals • of modules and accessories Screw-type terminals tightening torque of the screws in the bracket 20 N·m tightening torque [lbf-in] with screw-type terminals 8 8 lbf-in Lamp LED type of light source LED color of the light source white	 of the input voltage 	AC
• of the terminal IP20 Supply voltage AC type of voltage of the supply voltage of the light source AC supply voltage of the light source at AC at 60 Hz 6 V • rated value 6 V Inputs/ Outputs 6 V connections/ Terminals 5 crew-type terminals • of modules and accessories 5 crew-type terminals • of modules and accessories 5 crew-type terminals tightening torque of the screws in the bracket 20 N·m tightening torque [lbf-in] with screw-type terminals 8 8 lbf-in Lamp LED type of light source LED color of the light source white	surge voltage resistance rated value	4 kV
Supply voltage type of voltage of the supply voltage of the light source AC supply voltage of the light source at AC at 60 Hz 6 V • rated value 6 V Inputs/ Outputs 6 V output voltage 1 of the lamp transformer rated value 6 V Connections/ Terminals 5 crew-type terminals type of electrical connection screw-type terminals • of modules and accessories Screw-type terminal tightening torque of the screws in the bracket 20 N·m tightening torque [lbf-in] with screw-type terminals 8 8 lbf-in Lamp LED type of light source White	protection class IP	IP66
type of voltage of the supply voltage of the light source AC supply voltage of the light source at AC at 60 Hz 6 V • rated value 6 V Inputs/ Outputs 6 V output voltage 1 of the lamp transformer rated value 6 V Connections/ Terminals 6 V type of electrical connection screw-type terminals • of modules and accessories Screw-type terminal tightening torque of the screws in the bracket 20 N·m tightening torque [lbf-in] with screw-type terminals 8 8 lbf-in Lamp LED color of the light source White	• of the terminal	IP20
supply voltage of the light source at AC at 60 Hz 6 V • rated value 6 V Inputs/ Outputs 6 V output voltage 1 of the lamp transformer rated value 6 V Connections/ Terminals 6 V type of electrical connection screw-type terminals • of modules and accessories Screw-type terminal tightening torque of the screws in the bracket 20 N·m tightening torque [lbf-in] with screw-type terminals 8 8 lbf-in Lamp LED color of the light source White	Supply voltage	
• rated value 6 V Inputs/ Outputs 6 V output voltage 1 of the lamp transformer rated value 6 V Connections/ Terminals 6 V type of electrical connection screw-type terminals • of modules and accessories Screw-type terminal tightening torque of the screws in the bracket 20 N·m tightening torque [lbf·in] with screw-type terminals 8 8 lbf·in Lamp LED type of light source LED color of the light source white	type of voltage of the supply voltage of the light source	AC
Inputs/ Outputs 6 V connections/ Terminals 6 V type of electrical connection screw-type terminals • of modules and accessories Screw-type terminal tightening torque of the screws in the bracket 20 N·m tightening torque [lbf·in] with screw-type terminals 8 8 lbf·in Lamp LED color of the light source white	supply voltage of the light source at AC at 60 Hz	
output voltage 1 of the lamp transformer rated value 6 V Connections/ Terminals type of electrical connection screw-type terminals • of modules and accessories Screw-type terminal tightening torque of the screws in the bracket 20 N·m tightening torque [lbf-in] with screw-type terminals 8 8 lbf-in Lamp LED color of the light source white	rated value	6 V
Connections/ Terminals type of electrical connection screw-type terminals • of modules and accessories Screw-type terminal tightening torque of the screws in the bracket 20 N·m tightening torque [lbf·in] with screw-type terminals 8 8 lbf·in tamp LED tool of the light source white	Inputs/ Outputs	
type of electrical connection screw-type terminals • of modules and accessories Screw-type terminal tightening torque of the screws in the bracket 20 N·m tightening torque [lbf·in] with screw-type terminals 8 8 lbf·in Lamp LED tool of the light source white	output voltage 1 of the lamp transformer rated value	6 V
• of modules and accessories Screw-type terminal tightening torque of the screws in the bracket 20 N·m tightening torque [lbf-in] with screw-type terminals 8 8 lbf-in Lamp LED top of the light source white	Connections/ Terminals	
tightening torque of the screws in the bracket 20 N·m tightening torque [lbf·in] with screw-type terminals 8 8 lbf·in Lamp type of light source tool of the light source LED white terminal	type of electrical connection	screw-type terminals
tightening torque [lbf·in] with screw-type terminals 8 8 lbf·in Lamp type of light source color of the light source LED white the	 of modules and accessories 	Screw-type terminal
Lamp LED type of light source white	tightening torque of the screws in the bracket	20 N·m
type of light source LED color of the light source white	tightening torque [lbf·in] with screw-type terminals	8 8 lbf·in
color of the light source white	Lamp	
	type of light source	LED
Safety related data	color of the light source	white
	Safety related data	

touch protection against electrical shock	finger-safe
Ambient conditions	
ambient temperature	
during operation	-35 +70 °C
during storage	-40 +85 °C
Installation/ mounting/ dimensions	
shape of the installation opening	round
Certificates/ approvals	
Further information	
Siemens has decided to exit the Russian market (see here). https://press.siemens.com/global/en/pressrelease/siemens-wind-down-russian-business Siemens is working on the renewal of the current EAC certificates. Please contact your local Siemens office on the status of validity of the EAC certification if you intend to import or offer to supply these products to an EAC relevant market (other than the sanctioned EAEU member states Russia or Belarus). Information on the packaging https://support.industry.siemens.com/cs/ww/en/view/109813875 Information- and Downloadcenter (Catalogs, Brochures,) https://www.siemens.com/ic10 Industry Mall (Online ordering system) https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=US2:52PP3KBXB Cax online generator http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=US2:52PP3KBXB Service&Support (Manuals, Certificates, Characteristics, FAQs,) https://support.industry.siemens.com/cs/ww/en/ps/US2:52PP3KBXB Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros,)	

last modified:

5/31/2021 🖸