

Pushbutton Units and Indicator Lights

30 mm Heavy Duty, Watertight/Oiltight, Class 52

Push Pull Complete Units

Selection and ordering data

	Version	Color of actuator	Contact blocks	Order no.	List Price	Order no.	List Price	Pack
				Plastic Head	\$	Metal Head	\$	Unit
2 Position push-pull non-illuminated 	2 Position Push Pull, Maintained[Ⓛ] Non-Illuminated 1 3/4" (44.5 mm) mushroom head	less operating head	1NO - 1NC	52PP2WZA		52PP2AZA		1
		red	1NO - 1NC	52PP2W2A		52PP2A2A		
		green	1NO - 1NC	52PP2W3A		52PP2A3A		
		yellow	1NO - 1NC	52PP2W4A		—		
		chrome	1NO - 1NC	—		52PP2ACA		
	2 1/2" (63.5 mm) mushroom head	less operating head	1NO - 1NC	52PP2VZA				1
		red	1NO - 1NC	52PP2V2A				
		green	1NO - 1NC	52PP2V3A				
		yellow	1NO - 1NC	52PP2V4A				
		chrome	1NO - 1NC	—				
3 Position push-pull non-illuminated 	3 Position Push Pull, Momentary Non-Illuminated (Pull to start, push to stop) [Ⓛ] 1 3/4" (44.5 mm) mushroom head	less operating head	1NO - 1NC	52PP3WZU		52PP3AZU		1
		red	1NO - 1NC	52PP3W2U		52PP3A2U		
		green	1NO - 1NC	52PP3W3U		52PP3A3U		
		yellow	1NO - 1NC	52PP3W4U		—		
		chrome	1NO - 1NC	—		52PP3ACU		
	2 1/2" (63.5 mm) mushroom head	less operating head	1NO - 1NC	52PP3VZU				1
		red	1NO - 1NC	52PP3V2U				
		green	1NO - 1NC	52PP3V3U				
		yellow	1NO - 1NC	52PP3V4U				
		chrome	1NO - 1NC	—				
	3 Position Push Pull, Push Maintained, Pull Momentary Non-Illuminated (Pull to start, push to stop) [Ⓛ] 1 3/4" (44.5 mm) mushroom head	less operating head	1NO - 1NC	52PP7WZU		52PP7AZU		1
		red	1NO - 1NC	52PP7W2U		52PP7A2U		
		green	1NO - 1NC	52PP7W3U		52PP7A3U		
		yellow	1NO - 1NC	52PP7W4U		—		
		chrome	1NO - 1NC	—		52PP7ACU		
2 1/2" (63.5 mm) mushroom head	less operating head	1NO - 1NC	52PP7VZU				1	
	red	1NO - 1NC	52PP7V2U					
	green	1NO - 1NC	52PP7V3U					
	yellow	1NO - 1NC	52PP7V4U					
	chrome	1NO - 1NC	—					

Color options[Ⓜ]: black
blue
grey
orange

1
5
6
8

Ⓛ Blocks cannot be interchanged (start-stop circuit).

Ⓜ To order a color option, replace the 7th digit of the order number.

Ⓝ EMERGENCY-STOP control devices according to IEC 60947-5-5 when provided with red operating head and 52BJK contact blocks.