SIEMENS

Data sheet

US2:52PP7HSXB

30mm Command/52, Chrome Finish Heavy Duty,Watertight/Oiltight Complete Metal Unit Illuminated Push-Pull Operator Transformer type, 240V AC LED Lamp Mushroom Head Cap Small 1 3/4" (44.5 mm) Plastic, Green 3 Position Pull-Momentary/Push-Maintained UL Listed, CSA Certified NEMA 1,3,3R,4,4X,12,13 & Automotive Standards

design of the product Actuator round Enclosure 1 number of command points 1 delivery state as a kit No Actuator Product extension optional light source Yes material of the actuating element plastic plastic type of unlocking device pull-to-unlatch mechanism 1 number of switching positions 3 3 Front ring Yes 1 product component front ring Yes 1 design of the front ring standard 1 material of the front ring chrome 1 Holder Metal 1 1 material of the holder Metal 1 1 Display I 1 1 1
number of command points 1 delivery state as a kit No Actuator
delivery state as a kit No Actuator product extension optional light source Yes material of the actuating element plastic type of unlocking device pull-to-unlatch mechanism number of switching positions 3 Front ring Yes product component front ring Yes design of the front ring standard material of the front ring metal color of the front ring chrome Holder Metal Contact block/ lampholder Socket design socket design BA 9s with LED number of lampholders 1
Actuator product extension optional light source Yes material of the actuating element plastic type of unlocking device pull-to-unlatch mechanism number of switching positions 3 Front ring Yes product component front ring Yes design of the front ring standard material of the front ring metal color of the front ring chrome Holder Metal Contact block/ lampholder BA 9s with LED number of lampholders 1
product extension optional light sourceYesmaterial of the actuating elementplastictype of unlocking devicepull-to-unlatch mechanismnumber of switching positions3Front ringYesproduct component front ringYesdesign of the front ringstandardmaterial of the front ringmetalcolor of the front ringchromeHolderMetalcontact block/ lampholderBA 9s with LEDnumber of lampholders1
material of the actuating elementplastictype of unlocking devicepull-to-unlatch mechanismnumber of switching positions3Front ringYesproduct component front ringYesdesign of the front ringstandardmaterial of the front ringmetalcolor of the front ringchromeHolderMetalContact block/ lampholderBA 9s with LEDnumber of lampholders1
type of unlocking devicepull-to-unlatch mechanismnumber of switching positions3Front ringFront ringproduct component front ringYesdesign of the front ringstandardmaterial of the front ringmetalcolor of the front ringchromeHolderMetalcontact block/ lampholderBA 9s with LEDnumber of lampholders1
number of switching positions 3 Front ring Yes product component front ring standard design of the front ring standard material of the front ring metal color of the front ring chrome Holder Metal Contact block/ lampholder BA 9s with LED number of lampholders 1
Front ring Yes product component front ring Standard design of the front ring standard material of the front ring metal color of the front ring chrome Holder Metal Contact block/ lampholder BA 9s with LED number of lampholders 1
Front ring Yes design of the front ring standard material of the front ring metal color of the front ring chrome Holder Metal Contact block/ lampholder BA 9s with LED number of lampholders 1
product component front ring Yes design of the front ring standard material of the front ring metal color of the front ring chrome Holder Metal Contact block/ lampholder BA 9s with LED number of lampholders 1
material of the front ring metal color of the front ring chrome Holder Metal Contact block/ lampholder Socket design socket design BA 9s with LED number of lampholders 1
material of the front ring metal color of the front ring chrome Holder Metal Contact block/ lampholder Socket design socket design BA 9s with LED number of lampholders 1
color of the front ring chrome Holder Metal Contact block/ lampholder Metal socket design BA 9s with LED number of lampholders 1
Holder Metal contact block/ lampholder BA 9s with LED number of lampholders 1
Contact block/ lampholder BA 9s with LED number of lampholders 1
Contact block/ lampholder BA 9s with LED number of lampholders 1
socket design BA 9s with LED number of lampholders 1
number of lampholders 1
•
number of LED modules 1
General technical data
product component
Important Important Yes
Ight source Yes
degree of pollution 1
type of voltage
of the operating voltage AC
• of the input voltage AC
protection class IP of the terminal IP66 IP20
• of the terminal IP20
Cumplus valtage
Supply voltage
type of voltage of the supply voltage of the light source AC
type of voltage of the supply voltage of the light source AC supply voltage of the light source at AC at 60 Hz AC
type of voltage of the supply voltage of the light source AC supply voltage of the light source at AC at 60 Hz 6 V
type of voltage of the supply voltage of the light source AC supply voltage of the light source at AC at 60 Hz 6 V • rated value 6 V
type of voltage of the supply voltage of the light source AC supply voltage of the light source at AC at 60 Hz 6 V • rated value 6 V Inputs/ Outputs 6 V
type of voltage of the supply voltage of the light source AC supply voltage of the light source at AC at 60 Hz 6 V • rated value 6 V Inputs/ Outputs 6 V output voltage 1 of the lamp transformer rated value 6 V Connections/ Terminals 6 V
type of voltage of the supply voltage of the light source AC supply voltage of the light source at AC at 60 Hz 6 V • rated value 6 V Inputs/ Outputs 6 V
type of voltage of the supply voltage of the light source AC supply voltage of the light source at AC at 60 Hz 6 V • rated value 6 V Inputs/ Outputs 6 V output voltage 1 of the lamp transformer rated value 6 V Connections/ Terminals 5 crew-type terminals • of modules and accessories 5 crew-type terminal
type of voltage of the supply voltage of the light source AC supply voltage of the light source at AC at 60 Hz 6 V • rated value 6 V Inputs/ Outputs 6 V output voltage 1 of the lamp transformer rated value 6 V Connections/ Terminals 5 crew-type terminals • of modules and accessories 5 crew-type terminals tightening torque of the screws in the bracket 20 N·m
type of voltage of the supply voltage of the light source AC supply voltage of the light source at AC at 60 Hz 6 V • rated value 6 V Inputs/ Outputs 6 V output voltage 1 of the lamp transformer rated value 6 V Connections/ Terminals 5 crew-type terminals • of modules and accessories 5 crew-type terminal
type of voltage of the supply voltage of the light source AC supply voltage of the light source at AC at 60 Hz 6 V • rated value 6 V Inputs/ Outputs 6 V output voltage 1 of the lamp transformer rated value 6 V Connections/ Terminals 5 crew-type terminals • of modules and accessories 5 crew-type terminal tightening torque of the screws in the bracket 20 N·m
type of voltage of the supply voltage of the light source AC supply voltage of the light source at AC at 60 Hz 6 V • rated value 6 V Inputs/ Outputs 6 V output voltage 1 of the lamp transformer rated value 6 V Connections/ Terminals 5 crew-type terminals • of modules and accessories 5 crew-type terminal tightening torque of the screws in the bracket 20 N·m tightening torque [lbf·in] with screw-type terminals 8 8 lbf·in
type of voltage of the supply voltage of the light source AC supply voltage of the light source at AC at 60 Hz 6 V • rated value 6 V Inputs/ Outputs 6 V output voltage 1 of the lamp transformer rated value 6 V Connections/ Terminals 6 V type of electrical connection screw-type terminals • of modules and accessories Screw-type terminal tightening torque of the screws in the bracket 20 N·m tightening torque [lbf·in] with screw-type terminals 8 8 lbf-in
type of voltage of the supply voltage of the light source AC supply voltage of the light source at AC at 60 Hz 6 V • rated value 6 V Inputs/ Outputs 6 V output voltage 1 of the lamp transformer rated value 6 V Connections/ Terminals 6 V type of electrical connection screw-type terminals • of modules and accessories Screw-type terminal tightening torque of the screws in the bracket 20 N·m tightening torque [lbf-in] with screw-type terminals 8 8 lbf-in Lamp LED

Ambient conditions		
ambient temperature		
 during operation 	-35 +70 °C	
during storage	-40 +85 °C	
Installation/ mounting/ dimensions		
shape of the installation opening	round	
Certificates/ approvals		
Further information		
Siemens has decided to exit the Russian market (see here). https://press.siemens.com/global/en/pressrelease/siemens-wind-down-russian-business Siemens is working on the renewal of the current EAC certificates. Please contact your local Siemens office on the status of validity of the EAC certification if you intend to import or offer to supply these products to an EAC relevant market (other than the sanctioned EAEU member states Russia or Belarus). Information on the packaging		
https://support.industry.siemens.com/cs/ww/en/view/109813875 Information- and Downloadcenter (Catalogs, Brochures,) https://www.siemens.com/ic10 Industry Mall (Online ordering system) https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=US2:52PP7HSXB Cax online generator		
http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=US2:52PP7HSXB		
Service&Support (Manuals, Certificates, Characteristics, FAQs,) https://support.industry.siemens.com/cs/ww/en/ps/US2:52PP7HSXB		
Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros,) http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=US2:52PP7HSXB⟨=en		

```
last modified:
```

5/31/2021 🖸