SIEMENS

Data sheet

US2:52PP7JA

30mm Command/52, Chrome Finish Heavy Duty,Watertight/Oiltight Complete Metal Unit Illuminated Push-Pull Operator Transformer type, 480V AC Incandescent Lamp Mushroom Head Cap Small 1 3/4" (44.5 mm) Metal, Chrome with Clear Lens 3 Position Pull-Momentary/Push-Maintained UL Listed, CSA Certified NEMA 1,3,3R,4,4X,12,13 & Automotive Standards

	Certified NEMA 1,3,3R,4,4X,12,13 & Automotive Standards	
design of the product	Actuator round	
Enclosure		
number of command points	1	
delivery state as a kit	No	
Actuator		
product extension optional light source	Yes	
material of the actuating element	metal mushroom head with plastic lens	
type of unlocking device	pull-to-unlatch mechanism	
number of switching positions	3	
Front ring		
product component front ring	Yes	
design of the front ring	standard	
material of the front ring	metal	
color of the front ring	chrome	
Holder		
material of the holder	Metal	
Contact block/ lampholder		
socket design	BA 9s with lamp	
number of lampholders	1	
Display		
number of LED modules	0	
General technical data		
product component		
lamp transformer	Yes	
light source	Yes	
degree of pollution	1	
type of voltage		
 of the operating voltage 	AC	
of the input voltage	AC	
surge voltage resistance rated value	4 kV	
protection class IP	IP66	
• of the terminal	IP20	
Supply voltage		
type of voltage of the supply voltage of the light source	AC	
supply voltage of the light source at AC at 60 Hz		
rated value	6 V	
Inputs/ Outputs		
output voltage 1 of the lamp transformer rated value	6 V	
Connections/ Terminals		
type of electrical connection	screw-type terminals	
 of modules and accessories 	Screw-type terminal	
tightening torque of the screws in the bracket	20 N·m	
tightening torque [lbf·in] with screw-type terminals	8 8 lbf·in	
Lamp		
type of light source	filament lamp	
color of the light source	clear	
Safety related data		
touch protection against electrical shock	finger-safe	

Ambient conditions	
ambient temperature	
during operation	-35 +70 °C
during storage	-40 +85 °C
nstallation/ mounting/ dimensions	
shape of the installation opening	round
Certificates/ approvals	Tound
Further information	
Siemens is working on the renewal of the current EAC certifica Please contact your local Siemens office on the status of validity of EAC relevant market (other than the sanctioned EAEU member stat Information on the packaging https://support.industry.siemens.com/cs/ww/en/view/109813875 Information- and Downloadcenter (Catalogs, Brochures,) https://www.siemens.com/ic10 Industry Mall (Online ordering system) https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb= Cax online generator http://support.automation.siemens.com/WW/CAXorder/default.aspx Service&Support (Manuals, Certificates, Characteristics, FAQs https://support.industry.siemens.com/cs/ww/en/ps/US2:52PP7JA Image database (product images, 2D dimension drawings, 3D r http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=US2	the EAC certification if you intend to import or offer to supply these products to an tes Russia or Belarus). =US2:52PP7JA :?lang=en&mlfb=US2:52PP7JA ;)

```
last modified:
```

5/31/2021 🖸