## **SIEMENS**

Data sheet US2:52PP7K2XB

30mm Command/52, Chrome Finish Heavy Duty,Watertight/Oiltight Complete Metal Unit Illuminated Push-Pull Operator Transformer type, 600V AC LED Lamp Mushroom Head Cap Small 1 3/4" (44.5 mm) Metal, Chrome with Red Lens 3 Position Pull-Momentary/Push-Maintained UL Listed, CSA Certified NEMA 1,3,3R,4,4X,12,13 & Automotive Standards

	1,3,3R,4,4X,12,13 & Automotive Standards
design of the product	Actuator round
Enclosure	
number of command points	1
delivery state as a kit	No
Actuator	
product extension optional light source	Yes
material of the actuating element	metal mushroom head with plastic lens
type of unlocking device	pull-to-unlatch mechanism
number of switching positions	3
Front ring	
product component front ring	Yes
design of the front ring	standard
material of the front ring	metal
color of the front ring	chrome
Holder	
material of the holder	Metal
Contact block/ lampholder	
socket design	BA 9s with LED
number of lampholders	1
Display	
number of LED modules	1
General technical data	
product component	
lamp transformer	Yes
• light source	Yes
degree of pollution	1
type of voltage	
of the operating voltage	AC
of the input voltage	AC
surge voltage resistance rated value	4 kV
protection class IP	IP66
• of the terminal	IP20
Supply voltage	11 20
type of voltage of the supply voltage of the light source	AC
supply voltage of the light source at AC at 60 Hz	AC
• rated value	6 V
Inputs/ Outputs	V V
output voltage 1 of the lamp transformer rated value	6 V
Connections/ Terminals	0 V
type of electrical connection	screw type terminals
	screw-type terminals
of modules and accessories  tightening targue of the corous in the bracket.	Screw-type terminal 20 N·m
tightening torque of the screws in the bracket tightening torque [lbf-in] with screw-type terminals	8 8 lbf·in
	U U IUI'III
Lamp	LED
type of light source	LED
color of the light source	red
Safety related data	
touch protection against electrical shock	finger-safe

Ambient conditions	
ambient temperature	
<ul> <li>during operation</li> </ul>	-35 +70 °C
<ul> <li>during storage</li> </ul>	-40 +85 °C
Installation/ mounting/ dimensions	
shape of the installation opening	round
Certificates/ approvals	
E 0 1 5 C	

Siemens has decided to exit the Russian market (see here).

https://press.siemens.com/global/en/pressrelease/siemens-wind-down-russian-business

Siemens is working on the renewal of the current EAC certificates.

Please contact your local Siemens office on the status of validity of the EAC certification if you intend to import or offer to supply these products to an EAC relevant market (other than the sanctioned EAEU member states Russia or Belarus).

Information on the packaging

https://support.industry.siemens.com/cs/ww/en/view/109813875

Information- and Downloadcenter (Catalogs, Brochures,...)

https://www.siemens.com/ic10

Industry Mall (Online ordering system)

https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=US2:52PP7K2XB

Cax online generator

http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=US2:52PP7K2XB

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

https://support.industry.siemens.com/cs/ww/en/ps/US2:52PP7K2XB

 $Image\ database\ (product\ images,\ 2D\ dimension\ drawings,\ 3D\ models,\ device\ circuit\ diagrams,\ EPLAN\ macros,\ ...)$ 

 $\underline{\text{http://www.automation.siemens.com/bilddb/cax\_de.aspx?mlfb=US2:52PP7K2XB\&lang=en}}$ 

last modified:	5/31/2021	3
----------------	-----------	---