## SIEMENS

## Data sheet

## US2:52PP7V1U



30mm Command/52, Chrome Finish Heavy Duty, Watertight/Oiltight Complete Metal Unit Push-Pull Operator Non-Illuminated Mushroom Head Cap Large 2 1/2" (63.5 mm) Plastic, Black 3 Position Pull-Momentary/Push-Maintained 1 N.C.+1 N.C. Extra Late Break Heavy Duty Contacts, A600/P600 UL Listed, CSA Certified NEMA 1,3,3R,4,4X,12,13 & Automotive Standards

Figuresimilar

Enclosure		
number of command points	1	
delivery state as a kit	No	
Actuator		
color of the actuating element	black	
material of the actuating element	plastic	
number of contact modules	2	
type of unlocking device	pull-to-unlatch mechanism	
number of switching positions	3	
Front ring		
product component front ring	Yes	
design of the front ring	standard	
material of the front ring	metal	
General technical data		
product function positive opening	No	
product component		
light source	No	
insulation voltage rated value	600 V	
surge voltage resistance rated value	4 kV	
protection class IP	IP66	
<ul> <li>of the terminal</li> </ul>	IP20	
thermal current	10 A	
Auxiliary circuit		
number of NC contacts for auxiliary contacts	2	
number of NO contacts for auxiliary contacts	0	
operational current at AC-15		
<ul> <li>at 110 V rated value</li> </ul>	60 A	
• at 230 V rated value	30 A	
• at 400 V rated value	15 A	
• at 500 V rated value	12 A	
Connections/ Terminals		
type of electrical connection	screw-type terminals	
tightening torque of the screws in the bracket	20 N·m	
tightening torque [lbf·in] with screw-type terminals	8 lbf·in	
Ambient conditions		
ambient temperature		
<ul> <li>during operation</li> </ul>	-35 +70 °C	
during storage	-40 +85 °C	
Installation/ mounting/ dimensions		

shape of the installation opening	round
Certificates/ approvals	
Further information	
Siemens has decided to exit the Russian market (see here). https://press.siemens.com/global/en/pressrelease/siemens-wind-down-russian-business	
Siemens is working on the renewal of the current EAC certificates. Please contact your local Siemens office on the status of validity of the EAC certification if you intend to import or offer to supply these products to an EAC relevant market (other than the sanctioned EAEU member states Russia or Belarus).	
Information on the packaging https://support.industry.siemens.com/cs/ww/en/view/109813875	
Information- and Downloadcenter (Catalogs, Brochures,) https://www.siemens.com/ic10	
Industry Mall (Online ordering system) https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=US2:52PP7V1U	
Cax online generator http://support.automation.siemens.com/WW/CAXorder/default.aspx	?lang=en&mlfb=US2:52PP7V1U
Service&Support (Manuals, Certificates, Characteristics, FAQs	,)

https://support.industry.siemens.com/cs/ww/en/ps/US2:52PP7V1U Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...) http://www.automation.siemens.com/bilddb/cax\_de.aspx?mlfb=US2:52PP7V1U&lang=en

last modified:

5/31/2021 🖸