SIEMENS

Data sheet

US2:52PT6DBAB

30mm Command/52, Chrome Finish Heavy Duty,Watertight/Oiltight Complete Metal Unit PTT / Illuminated Pushbutton Full Voltage, 24V AC/DC LED Lamp Extended Button Plastic Lens, White 2 Position Momentary with 1 N.O. - 1 N.C. Heavy Duty Contacts, A600/P600 UL Listed, CSA Certified NEMA 1,3,3R,4,4X,12,13 & Automotive Standards



Figure similar

Enclosure		
number of command points	1	
delivery state as a kit	No	
Actuator		
product extension optional light source	Yes	
material of the actuating element	plastic	
number of contact modules	1	
type of unlocking device	without	
number of switching positions	2	
Front ring		
product component front ring	Yes	
design of the front ring	standard	
material of the front ring	metal	
Contact block/ lampholder		
number of lampholders	1	
Display		
number of LED modules	1	
General technical data		
product function positive opening	Yes	
product component		
 lamp transformer 	No	
light source	Yes	
insulation voltage rated value	600 V	
type of voltage		
 of the operating voltage 	AC/DC	
of the input voltage	AC/DC	
surge voltage resistance rated value	4 kV	
protection class IP	IP66	
• of the terminal	IP20	
thermal current	10 A	
Supply voltage		
type of voltage of the supply voltage of the light source	AC/DC	
supply voltage of the light source at AC at 60 Hz	20 0414	
• rated value	28 24 V	
supply voltage of the light source at DC	20 241/	
rated value	28 24 V	
Auxiliary circuit		
number of NC contacts for auxiliary contacts	1	
number of NO contacts for auxiliary contacts	1	

operational current at AC-15			
 at 110 V rated value 	60 A		
 at 230 V rated value 	30 A		
 at 400 V rated value 	15 A		
 at 500 V rated value 	12 A		
Connections/ Terminals			
type of electrical connection	screw-type terminals		
tightening torque of the screws in the bracket	20 N·m		
tightening torque [lbf·in] with screw-type terminals	8 8 lbf·in		
Lamp			
color of the light source	white		
Ambient conditions			
ambient temperature			
 during operation 	-35 +70 °C		
 during storage 	-40 +85 °C		
Installation/ mounting/ dimensions			
shape of the installation opening	round		
Certificates/ approvals			
Further information			
Information- and Downloadcenter (Catalogs, Brochures,) https://www.siemens.com/ic10 Industry Mall (Online ordering system) https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=US2:52PT6DBAB			
		Cax online generator	
		http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=US2:52PT6DBAB	
Service&Support (Manuals, Certificates, Characteristi	bttps://support.industry.siemens.com/cs/ww/en/os/US2:52PT6DBAB		

https://support.industry.siemens.com/cs/ww/en/ps/US2:52PT6DBAB Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...) http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=US2:52PT6DBAB&lang=en

last modified:

5/31/2021 🖸