SIEMENS

Data sheet

US2:52PX8A8H



30mm BlackMax, Epoxy Coated Corrosion Resistant Complete Metal Unit Pushbutton Non-Illuminated Flush Button Plastic Cap, Orange 2 Position Momentary with 1 N.O. Early Make Heavy Duty Contacts, A600/P600 UL Listed, CSA Certified NEMA 1,3,3R,4,4X,12,13 & Automotive Standards

-	÷		-	-	-	1
	IQ	ur	е	51	m	ilar
	-					

Enclosure				
number of command points	1			
delivery state as a kit	No			
Actuator				
design of the actuating element	Pushbutton			
material of the actuating element	plastic			
number of contact modules	1			
type of unlocking device	without			
number of switching positions	2			
Front ring				
product component front ring	Yes			
design of the front ring	standard			
material of the front ring	metal			
color of the front ring	black			
General technical data				
product function positive opening	No			
product component light source	No			
insulation voltage rated value	600 V			
surge voltage resistance rated value	4 kV			
protection class IP	IP66			
• of the terminal	IP20			
thermal current	10 A			
operating voltage				
• at AC at 60 Hz rated value	5 600 V			
• at DC rated value	5 600 V			
Auxiliary circuit				
number of NC contacts for auxiliary contacts	0			
number of NO contacts for auxiliary contacts	1			
operational current at AC-15				
• at 110 V rated value	60 A			
• at 230 V rated value	30 A			
• at 400 V rated value	15 A			
• at 500 V rated value	12 A			
Connections/ Terminals				
type of electrical connection	screw-type terminals			
tightening torque of the screws in the bracket	20 N·m			
tightening torque [lbf·in] with screw-type terminals	8 lbf-in			
Ambient conditions				
ambient temperature				

 during operation 	-35 +70 °C				
during storage	-40 +85 °C				
Installation/ mounting/ dimensions					
shape of the installation opening	round				
mounting height	21 mm				
installation width	48 mm				
installation depth	35 mm				
Certificates/ approvals					
Further information					
Siemens is working on the renewal of the current EAC certifica Please contact your local Siemens office on the status of validity of EAC relevant market (other than the sanctioned EAEU member sta Information on the packaging https://support.industry.siemens.com/cs/ww/en/view/109813875 Information- and Downloadcenter (Catalogs, Brochures,) https://www.siemens.com/ic10 Industry Mall (Online ordering system) https://mall.industry.siemens.com/mall/en/Catalog/product?mlfb: Cax online generator http://support.automation.siemens.com/WW/CAXorder/default.aspx Service&Support (Manuals, Certificates, Characteristics, FAQs https://support.industry.siemens.com/cs/ww/en/ps/US2:52PX8A8H Image database (product images, 2D dimension drawings, 3D of the status of	EVALUATE: The EAC certification if you intend to import or offer to supply these products to an ates Russia or Belarus). =US2:52PX8A8H <				

last modified:

6/1/2021 🖸