## SIEMENS

## Data sheet

## US2:52PX8B8F



30mm BlackMax, Epoxy Coated Corrosion Resistant Complete Metal Unit Pushbutton Non-Illuminated Extended Button Plastic Cap, Orange 2 Position Momentary with 2 N.O. Heavy Duty Contacts, A600/P600 UL Listed, CSA Certified NEMA 1,3,3R,4,4X,12,13 & Automotive Standards

Fi	gu	re	si	mi	lar

Enclosure	
number of command points	1
delivery state as a kit	No
Actuator	
design of the actuating element	Pushbutton
material of the actuating element	plastic
number of contact modules	2
type of unlocking device	without
number of switching positions	2
Front ring	
product component front ring	Yes
design of the front ring	standard
material of the front ring	metal
color of the front ring	black
General technical data	
product function positive opening	No
product component light source	No
insulation voltage rated value	600 V
surge voltage resistance rated value	4 kV
protection class IP	IP66
• of the terminal	IP20
thermal current	10 A
operating voltage	
• at AC at 60 Hz rated value	5 600 V
at DC rated value	5 600 V
Auxiliary circuit	
number of NC contacts for auxiliary contacts	0
number of NO contacts for auxiliary contacts	2
operational current at AC-15	
• at 110 V rated value	60 A
• at 230 V rated value	30 A
• at 400 V rated value	15 A
• at 500 V rated value	12 A
Connections/ Terminals	
type of electrical connection	screw-type terminals
tightening torque of the screws in the bracket	20 N·m
tightening torque [lbf·in] with screw-type terminals	8 lbf·in
Ambient conditions	
ambient temperature	

during operation	-35 +70 °C
during storage	-40 +85 °C
Installation/ mounting/ dimensions	
shape of the installation opening	round
mounting height	30 mm
installation width	54 mm
installation depth	35 mm
Certificates/ approvals	
Further information	
Siemens is working on the renewal of the current EAC certifica Please contact your local Siemens office on the status of validity of EAC relevant market (other than the sanctioned EAEU member sta Information on the packaging https://support.industry.siemens.com/cs/ww/en/view/109813875 Information- and Downloadcenter (Catalogs, Brochures,) https://www.siemens.com/ic10 Industry Mall (Online ordering system) https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb Cax online generator http://support.automation.siemens.com/WW/CAXorder/default.aspp Service&Support (Manuals, Certificates, Characteristics, FAQes https://support.industry.siemens.com/cs/ww/en/ps/US2:52PX888E Image database (product images, 2D dimension drawings, 3D http://www.automation.siemens.com/bilddb/cax.de.aspx?mlfb=US2	<pre>if the EAC certification if you intend to import or offer to supply these products to an ates Russia or Belarus). =US2:52PX8B8F x?lang=en&amp;mlfb=US2:52PX8B8F s,) models, device circuit diagrams, EPLAN macros,)</pre>

last modified:

6/1/2021 🖸