

Selectorswitch, metal Maintained, short lever 1NO left, right position, A Cam 2 position Complete device white insert Non-Illuminated UL file E22655 in Vol. 6 (7) Sec. 13 (2)



Figure similar

| Enclosure | |
|--|-----------------------------|
| number of command points | 1 |
| delivery state | |
| <ul style="list-style-type: none"> as a kit | No |
| Actuator | |
| material of the actuating element | plastic |
| number of contact modules | 1 |
| type of unlocking device | rotate-to-unlatch mechanism |
| number of switching positions | 2 |
| Front ring | |
| product component front ring | Yes |
| design of the front ring | standard |
| material of the front ring | metal |
| General technical data | |
| product function | |
| <ul style="list-style-type: none"> positive opening | No |

| | |
|------------------------------------|---------|
| product component | |
| • light source | No |
| insulation voltage | |
| • rated value | 600 V |
| protection class IP | IP66 |
| • of the terminal | IP20 |
| operating frequency maximum | 600 1/h |
| thermal current | 10 A |

Auxiliary circuit

| | |
|---|------|
| number of NC contacts for auxiliary contacts | 0 |
| number of NO contacts for auxiliary contacts | 1 |
| • operating current at AC-15 at 110 V rated value | 60 A |
| • operational current at AC-15 at 230 V rated value | 30 A |
| • operating current at AC-15 at 400 V rated value | 15 A |
| • operating current at AC-15 at 500 V rated value | 12 A |

Connections/ Terminals

| | |
|---|----------------------|
| type of electrical connection | screw-type terminals |
| tightening torque of the screws in the bracket | 20 N·m |
| tightening torque [lbf·in] | |
| • with screw-type terminals | 8 lbf·in |

Installation/ mounting/ dimensions

| | |
|--|-------|
| shape of the installation opening | round |
|--|-------|

Certificates/ approvals

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=US2:52SA2AABK1>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=US2:52SA2AABK1>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/US2:52SA2AABK1>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=US2:52SA2AABK1&lang=en

last modified:

10/09/2020