SIEMENS

Data sheet US2:52SB2DAB

	Selector switch, metal Maintained, long lever Position, D Cam 3 position Operator only white insert Non-Illuminated UL file E22655 in Vol. 6 (7) Sec. 13 (2)
design of the product	Actuator round
Enclosure	Actuator found
number of command points	1
delivery state as a kit	No
Actuator	NO
design of the actuating element	selector switch
material of the actuating element	plastic
shape of the actuating element	Extended handle
type of unlocking device	rotate-to-unlatch mechanism
number of switching positions	3
Front ring	
product component front ring	Yes
design of the front ring	standard
material of the front ring	metal
color of the front ring	chrome
Holder	CHOILE
material of the holder	Metal
General technical data	
product component	
• light source	No
degree of pollution	1
protection class IP	IP66
operating frequency maximum	600 1/h
Ambient conditions	
ambient temperature	
during operation	-35 +70 °C
during storage	-40 +85 °C
Installation/ mounting/ dimensions	
shape of the installation opening	round
Certificates/ approvals	
Further information	

Siemens has decided to exit the Russian market (see here).

 $\underline{\text{https://press.siemens.com/global/en/pressrelease/siemens-wind-down-russian-business}}$

Siemens is working on the renewal of the current EAC certificates.

Please contact your local Siemens office on the status of validity of the EAC certification if you intend to import or offer to supply these products to an EAC relevant market (other than the sanctioned EAEU member states Russia or Belarus).

Information on the packaging

https://support.industry.siemens.com/cs/ww/en/view/109813875

Information- and Downloadcenter (Catalogs, Brochures,...)

https://www.siemens.com/ic10

Industry Mall (Online ordering system)

https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=US2:52SB2DAB

Cax online generator

 $\underline{http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en\&mlfb=US2:52SB2DABarrows.com/WW/CAXorder/default.aspx?lang=en\&mlfb=US2:52SB2DABarrows.com/WW/CAXorder/default.aspx?lang=en\&mlfb=US2:52SB2DABarrows.com/WW/CAXorder/default.aspx?lang=en\&mlfb=US2:52SB2DABarrows.com/WW/CAXorder/default.aspx?lang=en\&mlfb=US2:52SB2DABarrows.com/WW/CAXorder/default.aspx?lang=en\&mlfb=US2:52SB2DABarrows.com/WW/CAXorder/default.aspx?lang=en\&mlfb=US2:52SB2DABarrows.com/WW/CAXorder/default.aspx?lang=en\&mlfb=US2:52SB2DABarrows.com/WW/CAXorder/default.aspx?lang=en\&mlfb=US2:52SB2DABarrows.com/WW/CAXorder/default.aspx?lang=en\&mlfb=US2:52SB2DABarrows.com/WW/CAXorder/default.aspx?lang=en\&mlfb=US2:52SB2DABarrows.com/WW/CAXorder/default.aspx?lang=en\&mlfb=US2:52SB2DABarrows.com/WW/CAXorder/default.aspx.$

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

https://support.industry.siemens.com/cs/ww/en/ps/US2:52SB2DAB

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=US2:52SB2DAB&lang=en

last modified: 5/31/2021