SIEMENS

Data sheet

US2:52SC6AEX298

	Metal, keyed selector switch Maintained, key type position, A Cam Operator only 2 position 550ch, key removable all Non-Illuminated UL file E22655 in Vol. 6 (7) Sec. 13 (2)
design of the product	Actuator round
Enclosure	
number of command points	1
delivery state as a kit	No
Actuator	
design of the actuating element	Key-operated switch
material of the actuating element	metal
type of unlocking device	key unlatching
number of switching positions	2
switch position for key distraction	removable in every position
lock make	ILLINOIS
key number	550CH
Front ring	
product component front ring	Yes
design of the front ring	standard
material of the front ring	metal
color of the front ring	chrome
Holder	Giromo
material of the holder	Metal
General technical data	Weta
product component	No
Ight source	1
degree of pollution	
protection class IP	IP66
operating frequency maximum	600 1/h
Ambient conditions	
ambient temperature	
during operation	-35 +70 °C
during storage	-40 +85 °C
Installation/ mounting/ dimensions	
shape of the installation opening	round
Certificates/ approvals	
Further information	
Siemens has decided to exit the Russian market (see here). https://press.siemens.com/global/en/pressrelease/siemens-wind-down-russian-business	
Siemens is working on the renewal of the current EAC certificates. Please contact your local Siemens office on the status of validity of the EAC certification if you intend to import or offer to supply these products to an EAC relevant market (other than the sanctioned EAEU member states Russia or Belarus). Information on the packaging https://support.industry.siemens.com/cs/ww/en/view/109813875 Information- and Downloadcenter (Catalogs, Brochures,) https://www.siemens.com/ic10	
Industry Mall (Online ordering system) https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=US2:52SC6AEX298 Cax online generator	
http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=US2:52SC6AEX298 Service&Support (Manuals, Certificates, Characteristics, FAQs,) https://support.industry.siemens.com/cs/ww/en/ps/US2:52SC6AEX298 Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros,) http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=US2:52SC6AEX298⟨=en	

last modified:

5/31/2021 🖸

Subject to change without notice © Copyright Siemens