

Metal, keyed selector switch Spring return from right position, A Cam Operator only  
Key removable in left position 2 position key type 506CH Non-Illuminated UL file  
E22655 in Vol. 6 (7) Sec. 13 (2)

|   |                     |
|---|---------------------|
| design of the product                     | Actuator round      |
| <b>Enclosure</b>                          |                     |
| number of command points                  | 1                   |
| delivery state as a kit                   | No                  |
| <b>Actuator</b>                           |                     |
| design of the actuating element           | Key-operated switch |
| material of the actuating element         | metal               |
| type of unlocking device                  | without             |
| number of switching positions             | 2                   |
| switch position for key distraction       | center              |
| lock make                                 | ILLINOIS            |
| key number                                | 506CH               |
| <b>Front ring</b>                         |                     |
| product component front ring              | Yes                 |
| design of the front ring                  | standard            |
| material of the front ring                | metal               |
| color of the front ring                   | chrome              |
| <b>Holder</b>                             |                     |
| material of the holder                    | Metal               |
| <b>General technical data</b>             |                     |
| product component                         |                     |
| • light source                            | No                  |
| degree of pollution                       | 1                   |
| protection class IP                       | IP66                |
| operating frequency maximum               | 600 1/h             |
| <b>Ambient conditions</b>                 |                     |
| ambient temperature                       |                     |
| • during operation                        | -35 ... +70 °C      |
| • during storage                          | -40 ... +85 °C      |
| <b>Installation/ mounting/ dimensions</b> |                     |
| shape of the installation opening         | round               |
| <b>Certificates/ approvals</b>            |                     |
| <b>Further information</b>                |                     |

Siemens has decided to exit the Russian market (see here).

<https://press.siemens.com/global/en/pressrelease/siemens-wind-down-russian-business>

Siemens is working on the renewal of the current EAC certificates.

Please contact your local Siemens office on the status of validity of the EAC certification if you intend to import or offer to supply these products to an EAC relevant market (other than the sanctioned EAEU member states Russia or Belarus).

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=US2:52SC6AXX302>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=US2:52SC6AXX302>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/US2:52SC6AXX302>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=US2:52SC6AXX302&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=US2:52SC6AXX302&lang=en)

