

Keyed selector switch, metal Maintained C Cam 3 position Operator only Non-Illuminated Key type 501CH (standard) Key removable center position UL file E22655 in Vol. 6 (7) Sec. 13 (2)

design of the product	Actuator round
-----------------------	----------------

### Enclosure

number of command points	1
delivery state	No
<ul style="list-style-type: none"> <li>as a kit</li> </ul>	No

### Actuator

design of the operating mechanism	Key-operated switch
material of the actuating element	metal
type of unlocking device	key unlatching
number of switching positions	3
switch position for key distraction	center
lock make	ILLINOIS
key number	501CH

### Front ring

product component front ring	Yes
design of the front ring	standard
material of the front ring	metal
color of the front ring	chrome

### Holder

material of the holder	Metal
------------------------	-------

### General technical data

product component	No
<ul style="list-style-type: none"> <li>light source</li> </ul>	No
degree of pollution	1
protection class IP	IP66
operating frequency maximum	600 1/h

### Installation/ mounting/ dimensions

shape of the installation opening	round
-----------------------------------	-------

### Certificates/ approvals

### Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=US2:52SC6CH>

**Cax online generator**

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=US2:52SC6CH>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<https://support.industry.siemens.com/cs/ww/en/ps/US2:52SC6CH>

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)**

[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=US2:52SC6CH&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=US2:52SC6CH&lang=en)

last modified:

10/09/2020