

## Data sheet

US2:52SC6CJX301

30mm Command/52, Chrome Finish Heavy Duty, Watertight/Oiltight Metal Operator, Round Non-Illuminated Keyed Selector Switch 3 Position, C-CAM Maintained Lock type 547CH with 2 Keys Key Removable in Left & Right UL Listed, CSA Certified UL File E22655 in Vol. 6 (7) Sec. 13 (2) NEMA 1,3,3R,4,4X,12,13 & Automotive Standards	
design of the product	Actuator round
Enclosure	
number of command points	1
delivery state as a kit	No
Actuator	
design of the actuating element	Key-operated switch
material of the actuating element	metal
type of unlocking device	key unlatching
number of switching positions	3
switch position for key distraction	left & right
lock make	ILLINOIS
key number	547CH
Front ring	
product component front ring	Yes
design of the front ring	standard
material of the front ring	metal
color of the front ring	chrome
Holder	
material of the holder	Metal
General technical data	
product component	
• light source	No
degree of pollution	1
protection class IP	IP66
operating frequency maximum	600 1/h
Ambient conditions	
ambient temperature	
• during operation	-35 ... +70 °C
• during storage	-40 ... +85 °C
Installation/ mounting/ dimensions	
shape of the installation opening	round
Certificates/ approvals	
Further information	
Siemens has decided to exit the Russian market (see here). <a href="https://press.siemens.com/global/en/pressrelease/siemens-wind-down-russian-business">https://press.siemens.com/global/en/pressrelease/siemens-wind-down-russian-business</a>	
Siemens is working on the renewal of the current EAC certificates. Please contact your local Siemens office on the status of validity of the EAC certification if you intend to import or offer to supply these products to an EAC relevant market (other than the sanctioned EAEU member states Russia or Belarus).	
Information on the packaging <a href="https://support.industry.siemens.com/cs/ww/en/view/109813875">https://support.industry.siemens.com/cs/ww/en/view/109813875</a>	
Information- and Downloadcenter (Catalogs, Brochures,...) <a href="https://www.siemens.com/ic10">https://www.siemens.com/ic10</a>	
Industry Mall (Online ordering system) <a href="https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=US2:52SC6CJX301">https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=US2:52SC6CJX301</a>	
Cax online generator <a href="http://support.automation.siemens.com/WW/CAOrder/default.aspx?lang=en&amp;mlfb=US2:52SC6CJX301">http://support.automation.siemens.com/WW/CAOrder/default.aspx?lang=en&amp;mlfb=US2:52SC6CJX301</a>	
Service&Support (Manuals, Certificates, Characteristics, FAQs,...) <a href="https://support.industry.siemens.com/cs/ww/en/ps/US2:52SC6CJX301">https://support.industry.siemens.com/cs/ww/en/ps/US2:52SC6CJX301</a>	
Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...) <a href="http://www.automation.siemens.com/blddb/cax_de.aspx?mlfb=US2:52SC6CJX301&amp;lang=en">http://www.automation.siemens.com/blddb/cax_de.aspx?mlfb=US2:52SC6CJX301&amp;lang=en</a>	

---

last modified:

5/31/2021 