


BCDH-500HS- 9 GY - PCB connectors



5437415

<https://www.phoenixcontact.com/ca/products/5437415>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Commercial data

Item number	5437415
Packing unit	50 pc
Minimum order quantity	1 pc
Note	Made to order (non-returnable)
Product key	AAC1DS
GTIN	4046356467261
Weight per piece (including packing)	12.607 g
Weight per piece (excluding packing)	12.607 g
Country of origin	DE

BCDH-500HS- 9 GY - PCB connectors



5437415

<https://www.phoenixcontact.com/ca/products/5437415>

Technical data

Product properties

Type	Standard
Number of positions	9
Pitch	5 mm
Mounting flange	without
Pin layout	Linear pinning


Electrical properties

Maximum load current	10 A
Rated voltage (II/2)	400 V
Rated voltage (III/2)	320 V
Rated surge voltage (II/2)	4 kV
Rated surge voltage (III/2)	4 kV
Rated surge voltage (III/3)	4 kV

Connection data

Maximum load current	10 A
----------------------	------

Dimensions

Dimensional drawing	
Length of the solder pin	3.2 mm
Length	22.1 mm
Length of the solder pin	3.2 mm
Hole diameter	1.4 mm
Pitch	5 mm

Material specifications

Flammability rating according to UL 94	V0
Insulating material group	I
Insulating material	PA
Contact surface	Tin Sn

Mechanical properties

Mechanical data	
Open side panel	No

Standards and regulations

BCDH-500HS- 9 GY - PCB connectors



5437415

<https://www.phoenixcontact.com/ca/products/5437415>

Connection in acc. with standard	EN-VDE
----------------------------------	--------



Mounting

Mounting type	Wave soldering
Pin layout	Linear pinning

Packaging specifications

Type of packaging	packed in cardboard
-------------------	---------------------

Dimensional drawing



BCDH-500HS- 9 GY - PCB connectors



5437415

<https://www.phoenixcontact.com/ca/products/5437415>

Environmental product compliance

EU RoHS	
Fulfills EU RoHS substance requirements	Yes, No exemptions
China RoHS	
Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits
EU REACH SVHC	
REACH candidate substance (CAS No.)	No substance above 0.1 wt%

BCDH-500HS- 9 GY - PCB connectors



5437415

<https://www.phoenixcontact.com/ca/products/5437415>

Accessories

CR-BC-M - Coding section

5436157

<https://www.phoenixcontact.com/ca/products/5436157>

Coding section



MSTB-BL - Accessories

1755477

<https://www.phoenixcontact.com/ca/products/1755477>

Keying cap, for forming sections, plugs onto header pin, green insulating material



BCDH-500HS- 9 GY - PCB connectors



5437415

<https://www.phoenixcontact.com/ca/products/5437415>

SK 5/3,8:FORTL.ZAHLEN - Marker card

0804183

<https://www.phoenixcontact.com/ca/products/0804183>



Marker card, white, labeled, horizontal: consecutive numbers 1 ... 10, 11 ... 20, etc. up to 91 ... (99)100, mounting type: adhesive, for terminal block width: 5 mm, lettering field size: 5 x 3.8 mm

SK U/3,8 WH:UNBEDRUCKT - Marker card

0803906

<https://www.phoenixcontact.com/ca/products/0803906>



Marker card, Din A4, white, unlabeled, can be labeled with: PLOTMARK, CMS-P1-PLOTTER, Office printing systems, mounting type: adhesive, for terminal block width: 210 mm, lettering field size: 186 x 3.8 mm, Number of individual labels: 1440

Phoenix Contact 2024 © - all rights reserved

<https://www.phoenixcontact.com>

PHOENIX CONTACT Ltd
8240 Parkhill Drive
Milton, Ontario L9T 5V7
1-800-890-2820
cdinfo@phoenixcontact.ca