


UMK 22-REL 12/21-21 - Relay Module



5542741
<https://www.phoenixcontact.com/us/products/5542741>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

VARIOFACE relay module, fixed, 2PDT



Your advantages

- Safe isolation between coil and contact side

Commercial data

| | |
|--------------------------------------|--------------------------------|
| Item number | 5542741 |
| Packing unit | 1 pc |
| Note | Made to order (non-returnable) |
| Sales key | C460 |
| Product key | CK61Y2 |
| GTIN | 4046356684217 |
| Weight per piece (including packing) | 33.33 g |
| Weight per piece (excluding packing) | 33.33 g |
| Customs tariff number | 85364190 |
| Country of origin | US |

UMK 22-REL 12/21-21 - Relay Module



5542741

<https://www.phoenixcontact.com/us/products/5542741>

Technical data

Notes

Trade restriction

| | |
|---------|--|
| CE note | The products are offered exclusively for export outside the EU and the European Economic Area. |
|---------|--|

Product properties

| | |
|-------------------------|---------------------------|
| Product type | Relay Module |
| Application | Universal |
| Operating mode | 100% operating factor |
| Mechanical service life | 1x 10 ⁷ cycles |

Electrical properties

| | |
|--------------------------------|--|
| Test voltage (Winding/contact) | 5 kV (50/60 Hz, 1 min., winding/contact) |
|--------------------------------|--|

Input data

Coil side

| | |
|---|--------------------|
| Nominal input voltage U _N | 12 V DC |
| Typical input current at U _N | 54 mA |
| Typical response time | 15 ms |
| Typical release time | 5 ms |
| Protective circuit | Freewheeling diode |
| Operating voltage display | LED |

Output data

Switching

| | |
|-----------------------------|-----------------------|
| Contact switching type | 2 changeover contacts |
| Contact material | AgCdO |
| Maximum switching voltage | 250 V AC (30 V DC) |
| Minimum switching voltage | 5 V (at 10 mA) |
| Limiting continuous current | 5 A |
| Min. switching current | 10 mA (At 5 V) |

Connection data

Coil side

| | |
|----------------------------------|--|
| Connection method | Screw connection |
| Stripping length | 7 mm |
| Conductor cross section rigid | 0.14 mm ² ... 2.5 mm ² |
| Conductor cross section flexible | 0.14 mm ² ... 1.5 mm ² |
| Conductor cross section AWG | 30 ... 14 |

Contact side

UMK 22-REL 12/21-21 - Relay Module



5542741

<https://www.phoenixcontact.com/us/products/5542741>

| | |
|----------------------------------|--|
| Connection method | Screw connection |
| Stripping length | 7 mm |
| Conductor cross section rigid | 0.14 mm ² ... 2.5 mm ² |
| Conductor cross section flexible | 0.14 mm ² ... 1.5 mm ² |
| Conductor cross section AWG | 30 ... 14 |

Dimensions

| | |
|--------|---------|
| Width | 22.5 mm |
| Height | 77 mm |
| Depth | 50 mm |

Material specifications

| | |
|-------|------------------|
| Color | green (RAL 6021) |
|-------|------------------|

Environmental and real-life conditions

Ambient conditions

| | |
|---|------------------|
| Ambient temperature (operation) | -20 °C ... 65 °C |
| Ambient temperature (storage/transport) | -40 °C ... 85 °C |

Mounting

| | |
|-----------------------|---------------------------|
| Assembly instructions | in rows with zero spacing |
| Mounting position | any |

UMK 22-REL 12/21-21 - Relay Module



5542741

<https://www.phoenixcontact.com/us/products/5542741>

Classifications

ECLASS

| | |
|-------------|----------|
| ECLASS-11.0 | 27371601 |
| ECLASS-12.0 | 27371601 |
| ECLASS-13.0 | 27371601 |

Environmental product compliance

| | |
|---|---|
| EU RoHS | |
| Fulfills EU RoHS substance requirements | Yes |
| Exemption | 7(a) |
| China RoHS | |
| Environment friendly use period (EFUP) | EFUP-50 |
| | An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required. |
| EU REACH SVHC | |
| REACH candidate substance (CAS No.) | Lead(CAS: 7439-92-1) |