

UMK 22-REL 240/21-21 - Relay Module




5543232

<https://www.phoenixcontact.com/us/products/5543232>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

VARIOFACE relay module, fixed, 1PDT



Your advantages

- Safe isolation between coil and contact side

Commercial data

Item number	5543232
Packing unit	1 pc
Note	Made to order (non-returnable)
Sales key	C460
Product key	CK6165
GTIN	4046356687102
Weight per piece (including packing)	33.33 g
Weight per piece (excluding packing)	33.33 g
Customs tariff number	85364190
Country of origin	ID

UMK 22-REL 240/21-21 - Relay Module



5543232

<https://www.phoenixcontact.com/us/products/5543232>

Technical data

Notes

Trade restriction

CE note	The products are offered exclusively for export outside the EU and the European Economic Area.
---------	--

Product properties

Product type	Relay Module
Application	Universal
Operating mode	100% operating factor
Mechanical service life	1x 10 ⁷ cycles

Electrical properties

Test voltage (Winding/contact)	5 kV (50/60 Hz, 1 min., winding/contact)
--------------------------------	--

Input data

Coil side

Nominal input voltage U _N	220 V AC
Typical input current at U _N	6 mA
Typical response time	15 ms
Typical release time	10 ms
Operating voltage display	Glow lamp

Output data

Switching

Contact switching type	2 changeover contacts
Contact material	AgCdO
Maximum switching voltage	250 V AC (30 V DC)
Minimum switching voltage	5 V (at 10 mA)
Limiting continuous current	5 A
Min. switching current	10 mA (At 5 V)

Connection data

Coil side

Connection method	Screw connection
Stripping length	7 mm
Conductor cross section rigid	0.14 mm ² ... 2.5 mm ²
Conductor cross section flexible	0.14 mm ² ... 1.5 mm ²
Conductor cross section AWG	30 ... 14

Contact side

Connection method	Screw connection
-------------------	------------------

UMK 22-REL 240/21-21 - Relay Module



5543232

<https://www.phoenixcontact.com/us/products/5543232>

Stripping length	7 mm
Conductor cross section rigid	0.14 mm ² ... 2.5 mm ²
Conductor cross section flexible	0.14 mm ² ... 1.5 mm ²
Conductor cross section AWG	30 ... 14

Dimensions

Width	22.5 mm
Height	77 mm
Depth	50 mm

Material specifications

Color	green (RAL 6021)
-------	------------------

Environmental and real-life conditions

Ambient conditions

Ambient temperature (operation)	-20 °C ... 65 °C
Ambient temperature (storage/transport)	-40 °C ... 85 °C

Mounting

Assembly instructions	in rows with zero spacing
Mounting position	any

UMK 22-REL 240/21-21 - Relay Module



5543232

<https://www.phoenixcontact.com/us/products/5543232>

Classifications

ECLASS

ECLASS-11.0	27371601
ECLASS-12.0	27371601
ECLASS-13.0	27371601

UMK 22-REL 240/21-21 - Relay Module



5543232
<https://www.phoenixcontact.com/us/products/5543232>

Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com