

https://www.phoenixcontact.com/us/products/5601975

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



VARIOFACE relay socket for 8-pin octal relay

## Your advantages

- Pluggable base for 8-pin octal style relays
- Safe isolation between coil and contact side
- 10 A, 2 PDT contact rating
- DIN rail mount

### Commercial data

Item number	5601975
Packing unit	1 pc
Note	Made to order (non-returnable)
Sales key	C460
Product key	CK61AY
GTIN	4046356687294
Weight per piece (including packing)	33.33 g
Weight per piece (excluding packing)	33.33 g
Customs tariff number	85364190
Country of origin	US

PHŒNIX

5601975

https://www.phoenixcontact.com/us/products/5601975



## Technical data

### Product properties

Application	Universal
Operating mode	100% operating factor
Electrical properties	
Nominal voltage U.	250 V AC/DC

Nominal voltage U <sub>N</sub>	250 V AC/DC
Nominal current I <sub>N</sub>	10 A

#### Connection data

Input side	
Connection method	Screw connection
Stripping length	8 mm
Screw thread	M3
Conductor cross section rigid	0.2 mm <sup>2</sup> 6 mm <sup>2</sup>
Conductor cross section flexible	0.2 mm <sup>2</sup> 4 mm <sup>2</sup>
Conductor cross section AWG	30 10
Output side	
Connection method	Screw connection
Stripping length	8 mm
Screw thread	M3
Conductor cross section rigid	0.2 mm <sup>2</sup> 6 mm <sup>2</sup>

#### Dimensions

Width	45 mm
Height	77 mm

0.2 mm<sup>2</sup> ... 4 mm<sup>2</sup>

30 ... 10

### Environmental and real-life conditions

Conductor cross section flexible

Conductor cross section AWG

Ambient conditions	
Ambient temperature (operation)	-20 °C 65 °C
Ambient temperature (storage/transport)	-40 °C 85 °C

#### Mounting

Mounting type	DIN rail mounting
Assembly instructions	in rows with zero spacing
Mounting position	any



https://www.phoenixcontact.com/us/products/5601975



# Classifications

#### ECLASS

ECLASS-11.0	27371603
ECLASS-12.0	27371603
ECLASS-13.0	27371603

#### ETIM

ETIM 9.0	EC001456
----------	----------

5601975

https://www.phoenixcontact.com/us/products/5601975



# Environmental product compliance

#### EU RoHS

Fulfills EU RoHS substance requirements	Yes
Exemption	7(a)
China RoHS	
Environment friendly use period (EFUP)	EFUP-50
	An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacture declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required.
EU REACH SVHC	
REACH candidate substance (CAS No.)	Lead(CAS: 7439-92-1)

Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com