

UM-DELTAV/A/SI/BFI/TP - Passive module



5603258

<https://www.phoenixcontact.com/pc/products/5603258>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Fuse module with separable test sockets, fuse failure display and shield connection terminals
(for analog cards of the Delta V control system)



Your advantages

- These system-specific interface modules for DeltaV modules are used in combination with the relevant system cables

Commercial data

Item number	5603258
Packing unit	1 pc
Minimum order quantity	1 pc
Note	Made to order (non-returnable)
Product key	CK21A2
Catalog page	Page 483 (C-5-2017)
GTIN	4017918955038
Weight per piece (including packing)	242.9 g
Weight per piece (excluding packing)	208.9 g
Customs tariff number	85369010
Country of origin	US

UM-DELTAV/A/SI/BFI/TP - Passive module



5603258

<https://www.phoenixcontact.com/pc/products/5603258>

Technical data

Product properties

Product type	Interface module
Product family	VARIOFACE
Number of positions	16
No. of channels	8

Electrical properties

Nominal voltage U_N	24 V DC
Max. current carrying capacity per branch	50 mA (in as-supplied state, with one 50 mAF fuse, max. 1 A permitted)

Supported controller EMERSON DeltaV

Suitable I/O card	VE4003S2B4
	VE4005S2B3
	VE4003S2B5
	SE4003S2B4

Connection data

Field level

Connection method	Screw connection
Stripping length	7 mm
Screw thread	M3
Conductor cross section rigid	0.2 mm ² ... 4 mm ²
Conductor cross section flexible	0.2 mm ² ... 2.5 mm ²
Conductor cross section AWG	24 ... 12

Controller level

Connection method	IDC/FLK pin strip
Number of connections	1
Number of positions	16
Pitch	2.54 mm

Signaling

Status display present	Yes, if the fuse fails
------------------------	------------------------

Dimensions

Item dimensions

Width	61 mm
Height	126 mm
Depth	71 mm

Material specifications

UM-DELTAV/A/SI/BFI/TP - Passive module



5603258

<https://www.phoenixcontact.com/pc/products/5603258>

Housing insulation material	Polyamide PA non-reinforced
-----------------------------	-----------------------------

Environmental and real-life conditions

Ambient conditions

Ambient temperature (operation)	-20 °C ... 50 °C
Ambient temperature (storage/transport)	-20 °C ... 70 °C

Standards and regulations

Standards/regulations	IEC 60664
	DIN EN 50178

Mounting

Mounting type	DIN rail mounting
Mounting position	any

Notes

General	For proper use, the specifications of the installation directive (see Downloads) must be observed. For applications or use with third-party products, the specifications, and the safety and warning instructions of the respective third-party manufacturer must also be met.
---------	--

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstraße 8
D-32825 Blomberg
+49 (0) 5235-3 00
info@phoenixcontact.com