



NEOZED, fuse base, D01, 1-pole, 16 A, Un AC: 400 V, Un DC: 250 V with twofold frame terminal

Model		
product brand name	NEOZED	
product designation	Fuse base	
design of the product	NEOZED fuse base installation	
General technical data		
number of poles	1	
size of fuse system according to EN 60269-1	D01	
Supply voltage		
operating voltage rated value	400 V	
Dissipation		
power loss [W] for rated value of the current at AC in hot operating state per pole	0.2 W	
operational current		
• at 35 °C rated value	15.36 A	
• at 40 °C rated value	15.04 A	
• at 45 °C rated value	14.72 A	
• at 50 °C rated value	14.4 A	
• at 55 °C rated value	14.08 A	
• at 60 °C rated value	13.76 A	
• at 65 °C rated value	13.28 A	
• at 70 °C rated value	12.96 A	
Main circuit		
operational current rated value	16 A	
Product details		
product component cover	Yes	
Mechanical Design		
height	83 mm	
width	27 mm	
depth	64 mm	
fastening method	DIN rail	
net weight	130 g	
material of D fuse base	plastic	
General Product Approval		Test Certificates
Declaration of Conformity		

[Confirmation](#)



[Type Test Certificates/Test Report](#)

[Miscellaneous](#)**Further information**

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5SG1301>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/5SG1301>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5SG1301

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>





