



NEOZED, fuse base, D02, 1-pole, 63 A, Un AC: 400 V, Un DC: 250 V with twofold frame terminal

| Model                                                                               |                               |                   |
|-------------------------------------------------------------------------------------|-------------------------------|-------------------|
| product brand name                                                                  | NEOZED                        |                   |
| product designation                                                                 | Fuse base                     |                   |
| design of the product                                                               | NEOZED fuse base installation |                   |
| General technical data                                                              |                               |                   |
| number of poles                                                                     | 1                             |                   |
| size of fuse system according to EN 60269-1                                         | D02                           |                   |
| Supply voltage                                                                      |                               |                   |
| operating voltage rated value                                                       | 400 V                         |                   |
| Dissipation                                                                         |                               |                   |
| power loss [W] for rated value of the current at AC in hot operating state per pole | 1 W                           |                   |
| operational current                                                                 |                               |                   |
| • at 35 °C rated value                                                              | 60.48 A                       |                   |
| • at 40 °C rated value                                                              | 59.22 A                       |                   |
| • at 45 °C rated value                                                              | 57.96 A                       |                   |
| • at 50 °C rated value                                                              | 56.7 A                        |                   |
| • at 55 °C rated value                                                              | 55.44 A                       |                   |
| • at 60 °C rated value                                                              | 54.18 A                       |                   |
| • at 65 °C rated value                                                              | 52.29 A                       |                   |
| • at 70 °C rated value                                                              | 51.03 A                       |                   |
| Main circuit                                                                        |                               |                   |
| operational current rated value                                                     | 63 A                          |                   |
| Product details                                                                     |                               |                   |
| product component cover                                                             | Yes                           |                   |
| Mechanical Design                                                                   |                               |                   |
| height                                                                              | 83 mm                         |                   |
| width                                                                               | 27 mm                         |                   |
| depth                                                                               | 64 mm                         |                   |
| fastening method                                                                    | DIN rail                      |                   |
| net weight                                                                          | 126 g                         |                   |
| material of D fuse base                                                             | plastic                       |                   |
| General Product Approval                                                            |                               | Test Certificates |
| Declaration of Conformity                                                           |                               |                   |

[Confirmation](#)



[Type Test Certificates/Test Report](#)

[Miscellaneous](#)**Further information**

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5SG1701>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/5SG1701>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=5SG1701](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5SG1701)

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>





