



NEOZED, fuse base, D02, 3-pole, 63 A, Un AC: 400 V, Un DC: 250 V with twofold frame terminal

Model		
product brand name	NEOZED	
product designation	Fuse base	
design of the product	NEOZED fuse base installation	
General technical data		
number of poles	3	
size of fuse system according to EN 60269-1	D02	
Supply voltage		
operating voltage rated value	400 V	
Dissipation		
power loss [W] for rated value of the current at AC in hot operating state per pole	3 W	
operational current		
• at 35 °C rated value	60.48 A	
• at 40 °C rated value	59.22 A	
• at 45 °C rated value	57.96 A	
• at 50 °C rated value	56.7 A	
• at 55 °C rated value	55.44 A	
• at 60 °C rated value	54.18 A	
• at 65 °C rated value	52.29 A	
• at 70 °C rated value	51.03 A	
Main circuit		
operational current rated value	63 A	
Product details		
product component cover	Yes	
Mechanical Design		
height	83 mm	
width	81 mm	
depth	64 mm	
fastening method	DIN rail	
net weight	380 g	
material of D fuse base	plastic	
General Product Approval		Test Certificates
Declaration of Conformity		

[Confirmation](#)



[Type Test Certificates/Test Report](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5SG5701>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/5SG5701>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5SG5701

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>





