



Undervoltage release 230 V AC, with 6 terminals for miniature circuit breaker 5SL4, 5SY, 5SP RCBO 5SU1, FI 5SV (for 5SU1 handle coupler 5ST3805-1 is required)

Model		
product brand name	SENTRON	
product designation	Undervoltage release	
General technical data		
switching function ON-delay/instantaneous contact	No	
type of voltage of the operating voltage for actuation	AC	
Control current		
control supply voltage		
• at AC at 50 Hz rated value minimum	230 V	
• at AC at 50 Hz rated value maximum	230 V	
• at AC at 60 Hz rated value minimum	230 V	
• at AC at 60 Hz rated value maximum	230 V	
Suitability		
suitability for integration		
• motor starter protector	No	
• overload relay	No	
suitability for use		
• load switch	No	
• circuit breaker	No	
number of NC contacts	0	
number of NO contacts	2	
number of CO contacts	0	
Connections		
type of electrical connection	screw-type terminals	
Mechanical Design		
height	90 mm	
depth	70 mm	
net weight	114 g	
General Product Approval		other
Declaration of Conformity		

[Confirmation](#)

[Miscellaneous](#)



[Environmental Confirmations](#)

other	Railway
-------	---------

[Miscellaneous](#)

[Vibration and Shock](#)

[Confirmation](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5ST3040>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/5ST3040>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5ST3040

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>





