

Pin busbar touch-safe, 16 mm² 3-phase, 214 mm long can be cut, with end caps



Model		
product brand name	SENTRON	
product designation	Pin busbar	
design of the product	16 mm², 3PH L214mm	
General technical data		
phase number	3	
cross-section	16 mm²	
Main circuit		
operational current rated value	80 A	
Product details		
product feature insulated	Yes	
Connections		
type of electrical connection	Pin	
Mechanical Design		
width	18 mm	
length	214 mm	
net weight	119.46 g	
General Product Approval		Declaration of Conformity
		other

[Confirmation](#)

[Miscellaneous](#)



[Miscellaneous](#)

other

[Environmental Con-
firmations](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)
<http://www.siemens.com/lowvoltage/catalogs>
Industry Mall (Online ordering system)
<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5ST3708>
Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
<https://support.industry.siemens.com/cs/ww/en/ps/5ST3708>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)


http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5ST3708

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>



¹⁾ Pin spacings in MW (Modular widths, 1 MW = 18 mm).

