



Auxiliary current switch can be attached for residual current operated circuit breaker 5SM3 for 16 A to 80 A, 1 NO+1 NC

Model		
product brand name		SENTRON
product designation		auxiliary switches
design of the product		Mountable
design of the product factory mounted		No
Supply voltage		
operating voltage		230 V
• rated value		
Switching capacity		
switching capacity current rated value		6 A
Control current		
type of voltage of control voltage		AC/DC
Product details		
number of fault signal contacts		0
number of NC contacts		1
number of NO contacts		1
number of CO contacts		0
product extension can be mounted		residual current operated circuit breaker
product extension		Auxiliary current switch
Mechanical Design		
number of modular width units		1
net weight		54 g
General Product Approval	Declaration of Conformity	other



[Environmental Conformations](#)

[Miscellaneous](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5SW3300>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/5SW3300>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5SW3300

CAX-Online-Generator



