



CIRCUIT BREAKER T55 230/400V, 6KA,
1-POLE, A, 2A

General technical data:		
Current / for AC / rated value	A	2
Tripping characteristic class		A
Type of voltage		AC/DC
Supply voltage		
• for AC / rated value	V	400
• with single-phase operation / with AC / rated value		
• with multi-phase operation / with AC / rated value	V	400
Number of poles / note		1P
Switching capacity current		
• in accordance with IEC 60947-2 / rated value	kA	10
• acc. to EN 60898 / rated value	kA	6
Mounting depth	mm	55
Number of width units		1
mounting position		any
Degree of pollution		3
Overvoltage class		3
• according to DIN EN 61346-2		
• according to DIN EN 81346-2		F

Certificates/approvals:

General Product Approval		Declaration of Conformity	Test Certificates	other	
			Special Test Certificate	other	Environmental Confirmations
GOST	UL	EG-Konf.			

Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.de/lowvoltage/mall>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/5SX2102-5/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5SX2102-5

CAX-Online-Generator

<http://www.siemens.com/cax>

last change:

Aug 12, 2014