

CIRCUIT BREAKER T55 CURR. SENS 2-POLE, C, 2A
DC 440V 10KA, AC 400V 4,5KA

Model		
product brand name		SENTRON
General technical data		
Number of poles		2
Number of poles / Note		2P
Tripping characteristic class		C
circuit-breaker / Design		5SX5
Overvoltage category		3
Supply voltage		
Supply voltage frequency / rated value	Hz	50
Protection class		
Protection class IP		IP20, with connected conductors
Energy limiting class		3
Switching capacity		
Switching capacity current		
• acc. to EN 60898 / rated value	kA	4.5
Electricity		
rated current I _n / IEC, DIN/VDE / at 40 Cel	A	1.88
Current / at AC / rated value	A	2
Product details		
Product expansion / can be installed / supplementary devices		Yes
Product function		
Product function / neutral conductor switching		Yes
Mechanical Design		
Mounting position		any
Installation depth	mm	55
Number of width units		2
Certificates		
Equipment marking		
• acc. to DIN EN 61346-2		F
• acc. to DIN EN 81346-2		F

General Product Approval	Declaration of Conformity	Test Certificates			other
	 EG-Konf.	Typprüfbescheinigung/Werkzeugnis	sonstig	spezielle Prüfbescheinigungen	Umweltbestätigung

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://eb.automation.siemens.com/mall/en/WW/Catalog/Product/5SX52027>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/5SX52027/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5SX52027

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://ausschreibungstexte.siemens.com/tiplv>

last modified:

02.02.2016