



CIRCUIT BREAKER 400V 10KA, 3-POLE, C,  
1A, D=70MM

Similar to image

| Technical data:                                                                                     |    |       |
|-----------------------------------------------------------------------------------------------------|----|-------|
| Overvoltage class                                                                                   |    | 3     |
| type of voltage                                                                                     |    | AC/DC |
| Tripping characteristic class                                                                       |    | C     |
| Degree of pollution                                                                                 |    | 3     |
| Mounting depth                                                                                      | mm | 70    |
| Energy limiting class                                                                               |    | 3     |
| Number of poles                                                                                     |    | 3     |
| Number of pitch units for width                                                                     |    | 3     |
| Product function / n-switching                                                                      |    | No    |
| Supply voltage frequency / rated value                                                              | Hz | 50    |
| Breaking capacity current / [nicht versorgt - nach IEC 60947-2] / [nicht versorgt - Bemessungswert] | kA | 15    |
| Breaking capacity current / acc. to EN 60898 / rated value                                          | kA | 10    |
| Supply voltage / for AC / rated value                                                               | V  | 400   |
| Current / for AC / rated value                                                                      | A  | 1     |
| Protection class IP                                                                                 |    | IP 20 |
| Product extension / can be installed / supplementary device                                         |    | Yes   |
| power loss                                                                                          | W  | 3.6   |

#### Further information:

**Information- and Downloadcenter (Catalogs, Brochures,...)**

<http://www.siemens.com/lowvoltage/catalogs>

**Global Industry Mall (Online ordering system)**



<http://www.siemens.com/lowvoltage/mall>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<http://support.automation.siemens.com/WW/view/en/5SY4301-7/all>

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)**

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=5SY4301-7](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5SY4301-7)



last change:

Dec 21, 2010