

Specifications

Eaton 062491

Eaton Moeller® series SVB Thumb-grip, black, lockable with padlock, for P3

General specifications

PRODUCT NAME	Eaton Moeller® series SVB Accessory Handle
CATALOG NUMBER	062491
EAN	4015080624912
PRODUCT LENGTH/DEPTH	100 mm
PRODUCT HEIGHT	65 mm
PRODUCT WIDTH	65 mm
PRODUCT WEIGHT	0.12 kg
CERTIFICATIONS	UL/CSA certification not required
MODEL CODE	SVB-SW-P3

Features & Functions

COLOR	Black
FEATURES	Lockable
FITTED WITH:	Padlocking feature
LOCKING FACILITY	Lockable with a maximum of 3 padlocks
LOCKING MECHANISM	Lockable in the 0 (Off) position (interlock) Lockable in the 1 position (please enquire)

General

AMBIENT OPERATING TEMPERATURE - MIN	-25 °C
AMBIENT OPERATING TEMPERATURE - MAX	50 °C
DEGREE OF PROTECTION	NEMA Other
SUITABLE FOR	Switch disconnecter Only for main switch
SWITCHING ANGLE	90 °
TYPE	<ul style="list-style-type: none">• Assembly kit• Main switch assembly kit• With black rotary handle and black locking ring
USED WITH	T5-.../E, .../Z, .../I5 T5B-.../E, .../Z, .../I4

Design verification

EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT PVID 0 W

HEAT DISSIPATION CAPACITY PDISS 0 W

HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT PVID 0 W

RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN) 0 A

STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT PVS 0 W

10.2.2 CORROSION RESISTANCE Meets the product standard's requirements.

10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES Meets the product standard's requirements.

10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT Meets the product standard's requirements.

10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS Meets the product standard's requirements.

10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION Meets the product standard's requirements.

10.2.5 LIFTING Does not apply, since the entire switchgear needs to be evaluated.

10.2.6 MECHANICAL IMPACT Does not apply, since the entire switchgear needs to be evaluated.

10.2.7 INSCRIPTIONS Meets the product standard's requirements.

10.3 DEGREE OF PROTECTION OF ASSEMBLIES Does not apply, since the entire switchgear needs to be evaluated.

10.4 CLEARANCES AND CREEPAGE DISTANCES Meets the product standard's requirements.

10.5 PROTECTION AGAINST ELECTRIC SHOCK Does not apply, since the entire switchgear needs to be evaluated.

Resources

CATALOGUES [P Switch-disconnectors and T Rotary cam switches catalogue CA042001EN](#)

[eaton-industrial-switch-disconnectors-catalogue-ca008011en-en-gb.pdf](#)

DECLARATIONS OF CONFORMITY [DA-DC-00005081.pdf](#)

DRAWINGS [eaton-rotary-switches-interlock-svb-handle-3d-drawing.eps](#)

[eaton-rotary-switches-t0-main-switch-symbol.eps](#)

10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.
10.10 TEMPERATURE RISE	Not applicable.
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc

Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

Follow us on social media to get the latest product and support information.



© 2025 Eaton. All Rights Reserved.