



LOGO! 24CEO, LOGIC MODULE, WITHOUT DISPLAY, PU//O:
24V/24V/24V TRANS., 8 DI (4AI)/4 DO; MEM 400 BLOCKS
EXPANDABLE, ETHERNET BUILD IN WEB-SERVER, DATALOG
STANDARD MICRO SD CARD FOR LOGO! SOFT COMFORT V8
PREVIOS PROJECT USABEL

Installation type/mounting

Mounting	on 35 mm DIN rail, 4 spacing units wide
----------	---

Supply voltage

24 V DC	Yes
permissible range, lower limit (DC)	20.4 V
permissible range, upper limit (DC)	28.8 V

Time of day

Time switching clocks

• Number	190
• Power reserve	480 h

Digital inputs

Number of digital inputs	8; Of which 4 can be used in analog mode (0 to 10 V)
--------------------------	--

Digital outputs

Number of digital outputs	4; Transistor
Short-circuit protection	Yes; electrical (1 A)

Output current

• for signal "1" permissible range for 0 to 55 °C, max.	0.3 A
---	-------

EMC

Emission of radio interference acc. to EN 55 011

• Emission of radio interference acc. to EN 55 011 (limit class B)	Yes; Radio interference suppression according to EN55011, Limit Value Class B
--	---

Degree and class of protection

IP20	Yes
------	-----

Standards, approvals, certificates

CSA approval	Yes
--------------	-----

UL approval	Yes
FM approval	Yes
developed in accordance with IEC 61131	Yes
acc. to VDE 0631	Yes
Marine approval	
• Marine approval	Yes
Ambient conditions	
Operating temperature	
• min.	0 °C
• max.	55 °C
Dimensions	
Width	71.5 mm
Height	90 mm
Depth	58 mm
last modified:	21.08.2014