



SITOP PSU400M/DC/DC/600V/24V/20A

SITOP PSU400M 20 A DC/DC converter input: 600 V DC output: 24 V DC/20 A

Input	
type of the power supply network	DC voltage
supply voltage at AC	startup from 340 V DC; derating necessary at 300 ... 400 V DC and 824 ... 900 V DC
<ul style="list-style-type: none"><li>initial value</li></ul>	
supply voltage	600 ... 600 V
<ul style="list-style-type: none"><li>at DC</li></ul>	
input voltage	300 ... 900 V
<ul style="list-style-type: none"><li>at DC</li></ul>	
overvoltage overload capability	Shutdown at $V_{in} > 900 \text{ V DC}$
input current	0.85 A
<ul style="list-style-type: none"><li>at DC at rated input voltage 600 V</li></ul>	8 A
current limitation of inrush current at 25 °C maximum	0.02 A <sup>2</sup> ·s
I <sup>2</sup> t value maximum	yes, cut-off capacity 20 kA; L/R < 2 ms ("+" and "-" input)
fuse protection type	
Output	
voltage curve at output	Controlled, isolated DC voltage
output voltage at DC rated value	24 V
output voltage	
<ul style="list-style-type: none"><li>at output 1 at DC rated value</li></ul>	24 V
relative overall tolerance of the voltage	3 %
relative control precision of the output voltage	
<ul style="list-style-type: none"><li>on slow fluctuation of input voltage</li></ul>	0.3 %
<ul style="list-style-type: none"><li>on slow fluctuation of ohm loading</li></ul>	0.3 %
residual ripple	
<ul style="list-style-type: none"><li>maximum</li></ul>	150 mV
<ul style="list-style-type: none"><li>typical</li></ul>	30 mV
voltage peak	
<ul style="list-style-type: none"><li>maximum</li></ul>	200 mV
<ul style="list-style-type: none"><li>typical</li></ul>	100 mV
adjustable output voltage	24 ... 28.8 V
product function output voltage adjustable	Yes
type of output voltage setting	via potentiometer; max. 480 W
display version for normal operation	Green LED for 24 V OK, green flashing LED for start delay
type of signal at output	Relay contact (NO contact, rating 60 V DC/ 0.3 A; 30 V DC/1 A) for 24 V OK
behavior of the output voltage when switching on	No overshoot of $V_{out}$ (soft start)
response delay maximum	0.1 s; 10 s adjustable using switch
voltage increase time of the output voltage	
<ul style="list-style-type: none"><li>maximum</li></ul>	150 ms
output current	
<ul style="list-style-type: none"><li>rated value</li></ul>	20 A

<ul style="list-style-type: none"> <li>• rated range</li> </ul>	0 ... 20 A; +60 ... +70 °C: Derating 5.5%/K
supplied active power typical	480 W
short-term overload current	
<ul style="list-style-type: none"> <li>• on short-circuiting during the start-up typical</li> </ul>	40 A
<ul style="list-style-type: none"> <li>• at short-circuit during operation typical</li> </ul>	60 A
duration of overloading capability for excess current	
<ul style="list-style-type: none"> <li>• on short-circuiting during the start-up</li> </ul>	150 ms
<ul style="list-style-type: none"> <li>• at short-circuit during operation</li> </ul>	25 ms
constant overload current	
<ul style="list-style-type: none"> <li>• on short-circuiting during the start-up typical</li> </ul>	23 A
product feature	
<ul style="list-style-type: none"> <li>• bridging of equipment</li> </ul>	Yes; switchable characteristic
number of parallel-switched equipment resources for increasing the power	2
<b>Efficiency</b>	
efficiency in percent	95 %
power loss [W]	
<ul style="list-style-type: none"> <li>• at rated output voltage for rated value of the output current typical</li> </ul>	25 W
<b>Closed-loop control</b>	
relative control precision of the output voltage with rapid fluctuation of the input voltage by +/- 15% typical	1.5 %
relative control precision of the output voltage load step of resistive load 50/100/50 % typical	1.5 %
setting time	
<ul style="list-style-type: none"> <li>• load step 50 to 100% typical</li> </ul>	1 ms
<ul style="list-style-type: none"> <li>• load step 100 to 50% typical</li> </ul>	1 ms
setting time	
<ul style="list-style-type: none"> <li>• maximum</li> </ul>	5 ms
<b>Protection and monitoring</b>	
design of the overvoltage protection	< 33 V
response value current limitation typical	22 A
property of the output short-circuit proof	Yes
design of short-circuit protection	Alternatively, constant current characteristic approx. 22 A or latching shutdown
enduring short circuit current RMS value	
<ul style="list-style-type: none"> <li>• typical</li> </ul>	22 A
overcurrent overload capability in normal operation	overload capability 150 % I <sub>out</sub> rated up to 5 s/min
display version for overload and short circuit	LED yellow for "overload", LED red for "latching shutdown", red LED flashing for "Overtemperature"
<b>Safety</b>	
galvanic isolation between input and output	Yes
galvanic isolation	Protective extra low output voltage V <sub>out</sub> according to EN 60950-1 and EN 50178
operating resource protection class	Class I
protection class IP	IP20
<b>Approvals</b>	
certificate of suitability	
<ul style="list-style-type: none"> <li>• CE marking</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• UL approval</li> </ul>	Yes; cULus-Listed (UL 508, CSA C22.2 No. 107.1), File E197259
<ul style="list-style-type: none"> <li>• CSA approval</li> </ul>	Yes; cULus-Listed (UL 508, CSA C22.2 No. 107.1), File E197259
<ul style="list-style-type: none"> <li>• cCSAus, Class 1, Division 2</li> </ul>	No
<ul style="list-style-type: none"> <li>• ATEX</li> </ul>	No
certificate of suitability	
<ul style="list-style-type: none"> <li>• IECEx</li> </ul>	No
<ul style="list-style-type: none"> <li>• NEC Class 2</li> </ul>	No
<ul style="list-style-type: none"> <li>• ULhazloc approval</li> </ul>	No
<ul style="list-style-type: none"> <li>• FM registration</li> </ul>	No
type of certification CB-certificate	Yes
certificate of suitability	
<ul style="list-style-type: none"> <li>• EAC approval</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• C-Tick</li> </ul>	No
certificate of suitability shipbuilding approval	Yes
shipbuilding approval	DNV GL

Marine classification association	
• American Bureau of Shipping Europe Ltd. (ABS)	No
• French marine classification society (BV)	No
• DNV GL	Yes
• Lloyds Register of Shipping (LRS)	No
• Nippon Kaiji Kyokai (NK)	No
<b>EMC</b>	
standard	
• for emitted interference	EN 55022 Class A (emission)
• for mains harmonics limitation	-
• for interference immunity	EN 61000-6-2
<b>environmental conditions</b>	
ambient temperature	
• during operation	-25 ... +70 °C; with natural convection
• during transport	-40 ... +85 °C
• during storage	-40 ... +85 °C
environmental category according to IEC 60721	Climate class 3K3, 5 ... 95% no condensation
<b>Mechanics</b>	
type of electrical connection	screw-type terminals
• at input	DC input, +, -, PE: 1 screw terminal each for 0.2 ... 6/4 mm <sup>2</sup> single-core/finely stranded
• at output	+, -: 2 screw terminals each for 0.2 ... 6/4 mm <sup>2</sup> single-core/finely stranded
• for auxiliary contacts	Alarm signals: 2 screw terminals for 0.14 ... 1.5 mm <sup>2</sup> single-core/finely stranded
width of the enclosure	90 mm
height of the enclosure	125 mm
depth of the enclosure	125 mm
required spacing	
• top	50 mm
• bottom	50 mm
• left	0 mm
• right	0 mm
net weight	1.2 kg
product feature of the enclosure housing can be lined up	Yes
fastening method	Snaps onto DIN rail EN 60715 35x7.5/15
mechanical accessories	Device identification label 20 mm × 7 mm, pale turquoise 3RT1900-1SB20
MTBF at 40 °C	622 277 h
other information	Specifications at rated input voltage and ambient temperature +25 °C (unless otherwise specified)

