



Figure similar

*** spare part *** SIMATIC DP, interface module IM 151-1 Basic for ET 200S; transmission rate up to 12 Mbit/s; max. 12 power, electronic or motor starter modules (no F modules) can be connected; bus connection via 9-pin D-sub including termination module

General information

Product type designation	IM 151-1 Basic
Vendor identification (VendorID)	80F3h
Product function	
• Isochronous mode	No

Supply voltage

Mains buffering	
• Mains/voltage failure stored energy time	No

Input current

from supply voltage 1L+, max.	70 mA
-------------------------------	-------

Power loss

Power loss, typ.	1.5 W
------------------	-------

Address area

Addressing volume	
• Inputs	88 byte
• Outputs	88 byte

Interfaces

Transmission procedure	RS 485
Transmission rate, max.	12 Mbit/s; 9,6 / 19,2 / 45,45 / 93,75 / 187,5 / 500 kbit/s; 1,5 / 3 / 6 / 12 Mbit/s

1. Interface

Interface types	
• RS 485	Yes
• Output current of the interface, max.	80 mA
• Design of the connection	9-pin sub D socket

Protocols

Supports protocol for PROFINET IO	No
PROFIBUS DP	Yes
PROFIBUS DP	
Services	
— SYNC capability	Yes
— FREEZE capability	Yes
— Direct data exchange (slave-to-slave communication)	Yes

Interrupts/diagnostics/status information

Alarms	No
Diagnostics function	Yes
Diagnostics indication LED	
• Bus fault BF (red)	Yes

- Group error SF (red) Yes
- Monitoring 24 V voltage supply ON (green) Yes

Potential separation

between backplane bus and electronics	No
between electronic block and PROFIBUS DP	Yes
between supply voltage and electronics	No

Isolation

Isolation tested with	500 V DC
-----------------------	----------

Dimensions

Width	45 mm
Height	119.5 mm
Depth	75 mm

Weights

Weight, approx.	150 g
-----------------	-------

last modified: 3/11/2021 