



Figure similar

SIMATIC S7-1500, digital input module DI 32x24 V DC HF, 32 channels in groups of 16; of which 2 inputs as counters can be used; input delay 0.05..20 ms input type 3 (IEC 61131); diagnostics; hardware interrupts: front connector (screw terminals or push-in) to be ordered separately

General information	
Product type designation	DI 32x24VDC HF
HW functional status	from FS04
Firmware version	V2.2.1
• FW update possible	Yes
Product function	
• I&M data	Yes; I&M0 to I&M3
• Isochronous mode	Yes
• Prioritized startup	Yes
Engineering with	
• STEP 7 TIA Portal configurable/integrated from version	V13 SP1 / -
• STEP 7 configurable/integrated from version	V5.5 SP3 / -
• PROFIBUS from GSD version/GSD revision	V1.0 / V5.1
• PROFINET from GSD version/GSD revision	V2.3 / -
Operating mode	
• DI	Yes
• Counter	Yes
• Oversampling	No
• MSI	Yes
Supply voltage	
Rated value (DC)	24 V
permissible range, lower limit (DC)	19.2 V
permissible range, upper limit (DC)	28.8 V
Reverse polarity protection	Yes
Input current	
Current consumption, max.	40 mA; 20 mA per group with 24 V DC supply
Power	
Power available from the backplane bus	1.1 W
Power loss	
Power loss, typ.	4.2 W
Digital inputs	
Number of digital inputs	32
Digital inputs, parameterizable	Yes
Source/sink input	P-reading
Input characteristic curve in accordance with IEC 61131, type 3	Yes
Digital input functions, parameterizable	
• Gate start/stop	Yes
• Freely usable digital input	Yes

<ul style="list-style-type: none"> <li>Counter <ul style="list-style-type: none"> <li>Number, max.</li> <li>Counting frequency, max.</li> <li>Counting width</li> <li>Counting direction up/down</li> </ul> </li> </ul>	2 6 kHz; FS04 and FW V2.2.1 or higher 32 bit Up
<b>Input voltage</b>	
<ul style="list-style-type: none"> <li>Rated value (DC)</li> <li>for signal "0"</li> <li>for signal "1"</li> </ul>	24 V -30 to +5 V +11 to +30V
<b>Input current</b>	
<ul style="list-style-type: none"> <li>for signal "1", typ.</li> </ul>	2.5 mA
<b>Input delay (for rated value of input voltage)</b>	
<b>for standard inputs</b>	
<ul style="list-style-type: none"> <li>parameterizable</li> <li>at "0" to "1", min.</li> <li>at "0" to "1", max.</li> <li>at "1" to "0", min.</li> <li>at "1" to "0", max.</li> </ul>	Yes; 0.05 / 0.1 / 0.4 / 1.6 / 3.2 / 12.8 / 20 ms 0.05 ms 20 ms 0.05 ms 20 ms
<b>for interrupt inputs</b>	
<ul style="list-style-type: none"> <li>parameterizable</li> </ul>	Yes
<b>for technological functions</b>	
<ul style="list-style-type: none"> <li>parameterizable</li> </ul>	Yes
<b>Cable length</b>	
<ul style="list-style-type: none"> <li>shielded, max.</li> <li>unshielded, max.</li> </ul>	1 000 m 600 m
<b>Encoder</b>	
<b>Connectable encoders</b>	
<ul style="list-style-type: none"> <li>2-wire sensor <ul style="list-style-type: none"> <li>permissible quiescent current (2-wire sensor), max.</li> </ul> </li> </ul>	Yes 1.5 mA
<b>Isochronous mode</b>	
Filtering and processing time (TCI), min.	80 µs; At 50 µs filter time
Bus cycle time (TDP), min.	250 µs
<b>Interrupts/diagnostics/status information</b>	
Diagnostics function	Yes
<b>Alarms</b>	
<ul style="list-style-type: none"> <li>Diagnostic alarm</li> <li>Hardware interrupt</li> </ul>	Yes Yes
<b>Diagnoses</b>	
<ul style="list-style-type: none"> <li>Monitoring the supply voltage</li> <li>Wire-break</li> <li>Short-circuit</li> </ul>	Yes Yes; to I < 350 µA No
<b>Diagnostics indication LED</b>	
<ul style="list-style-type: none"> <li>RUN LED</li> <li>ERROR LED</li> <li>Monitoring of the supply voltage (PWR-LED)</li> <li>Channel status display</li> <li>for channel diagnostics</li> <li>for module diagnostics</li> </ul>	Yes; green LED Yes; red LED Yes; green LED Yes; green LED Yes; red LED Yes; red LED
<b>Potential separation</b>	
<b>Potential separation channels</b>	
<ul style="list-style-type: none"> <li>between the channels</li> <li>between the channels, in groups of</li> <li>between the channels and backplane bus</li> <li>between the channels and the power supply of the electronics</li> </ul>	Yes 16 Yes No
<b>Isolation</b>	
Isolation tested with	707 V DC (type test)
<b>Standards, approvals, certificates</b>	
Suitable for safety functions	No
<b>Ambient conditions</b>	
Ambient temperature during operation	

- horizontal installation, min. -30 °C; From FS05
- horizontal installation, max. 60 °C
- vertical installation, min. -30 °C; From FS05
- vertical installation, max. 40 °C

#### Altitude during operation relating to sea level

- Installation altitude above sea level, max. 5 000 m; Restrictions for installation altitudes > 2 000 m, see manual

#### Dimensions

Width	35 mm
Height	147 mm
Depth	129 mm

#### Weights

Weight, approx.	260 g
-----------------	-------

**last modified:** 7/30/2021 