



SIMATIC DP, CM PROFIBUS DP for ET 200SP CPU module with PROFIBUS DP interface (9-pole D-sub socket) DP master for 125 DP slaves DP slave,

General information	
Product type designation	CM PROFIBUS DP
HW functional status	FS04
Engineering with	
<ul style="list-style-type: none"> <li>STEP 7 TIA Portal configurable/integrated from version</li> </ul>	V13 Update 3
Supply voltage	
Rated value (DC)	24 V
permissible range, lower limit (DC)	19.2 V
permissible range, upper limit (DC)	28.8 V
Reverse polarity protection	Yes
1. Interface	
Interface types	
<ul style="list-style-type: none"> <li>RS 485</li> </ul>	Yes
Protocols	
<ul style="list-style-type: none"> <li>PROFIBUS DP master</li> <li>PROFIBUS DP slave</li> <li>SIMATIC communication</li> </ul>	Yes Yes Yes
PROFIBUS DP master	
<ul style="list-style-type: none"> <li>Number of DP slaves, max.</li> </ul>	125
Services	
<ul style="list-style-type: none"> <li>PG/OP communication</li> <li>Equidistance</li> <li>Isochronous mode</li> <li>Activation/deactivation of DP slaves</li> </ul>	Yes No No Yes
PROFIBUS DP slave	
<ul style="list-style-type: none"> <li>Transmission rate, max.</li> <li>automatic baud rate search</li> <li>Address area, max.</li> <li>User data per address area, max.</li> </ul>	12 Mbit/s Yes 120 128 byte
Services	
<ul style="list-style-type: none"> <li>PG/OP communication</li> <li>Routing</li> <li>S7 communication</li> <li>Direct data exchange (slave-to-slave communication)</li> <li>DPV1</li> </ul>	Yes; Only with active interface Yes; Only with active interface Yes; Only with active interface Yes; No subscriber possible - only passive publisher Yes
Transfer memory	
<ul style="list-style-type: none"> <li>Inputs</li> <li>Outputs</li> </ul>	244 byte 244 byte
Interface types	
RS 485	

• Transmission rate, max.	12 Mbit/s
• Cable length, max.	100 m
<b>Protocols</b>	
SIMATIC communication	
• S7 routing	Yes
• Data record routing	Yes
<b>Interrupts/diagnostics/status information</b>	
Diagnostics function	Yes
Diagnostics indication LED	
• for module diagnostics	Yes; green/red DIAG LED
<b>Potential separation</b>	
between backplane bus and interface	Yes
<b>Ambient conditions</b>	
Ambient temperature during operation	
• horizontal installation, min.	-25 °C; No condensation
• horizontal installation, max.	60 °C
• vertical installation, min.	-25 °C; No condensation
• vertical installation, max.	50 °C
Altitude during operation relating to sea level	
• Installation altitude above sea level, max.	5 000 m; Restrictions for installation altitudes > 2 000 m, see manual
<b>Dimensions</b>	
Width	35 mm
Height	117 mm
Depth	75 mm
<b>Weights</b>	
Weight, approx.	80 g
<b>last modified:</b>	12/16/2020 