SIEMENS

Data sheet

6GK1900-0MB00-6AA0

Product type designation Product description

IE SC RJ POF Plug PRO (Push Pull)

SC RJ connector for POF fibre optic cable IE SC RJ POF PLUG PRO, FO PLUG FOR ON-SITE MOUNTING TO POF FO CABLES (PACKAGING UNIT 1 DUPLEX-CONNECTOR)



Suitability for use	Field-assembly connector for push-pull device connection in high degree of protection	
Transmission rate		
Transfer rate / for Industrial Ethernet	100 Mbit/s	
Interfaces		
Number of optical interfaces / for fiber optic cable	1	
Design of the optical interface / for network	SC RJ connector (Push Pull device connection)	
components or terminal equipment		
Type of electrical connection / FastConnect	No	
Mechanical data		
Material / of the enclosure	plastic	
Locking mechanism design	Push-pull	
Design, dimensions and weight		
Type of cable outlet	180° cable outlet	
Width	22 mm	
Height	30 mm	
Depth	62.5 mm	

Net weight	63.5 g
Permitted ambient conditions	
Ambient temperature	
during operation	-40 +70 °C
during storage	-40 +70 °C
during transport	-40 +70 °C
Chemical resistance / to water	resistant
Protection class IP	IP65/67
Product properties, functions, components / general	
Product feature	
• silicon-free	Yes
Product component	
• strain relief	Yes
Standards, specifications, approvals	
Certificate of suitability	
 RoHS conformity 	Yes
• UL approval	No
 Railway application in accordance with EN 50155 	No
Further Information / Internet Links	
Internet-Link	
• to website: Selector SIMATIC NET SELECTION TOOL	http://www.siemens.com/snst
• to website: Industrial communication	http://www.siemens.com/simatic-net
• to website: Industry Mall	https://mall.industry.siemens.com
• to website: Information and Download Center	http://www.siemens.com/industry/infocenter

• to website: Image database

to website: CAx Download Managerto website: Industry Online Support

http://automation.siemens.com/bilddb

https://support.industry.siemens.com

http://www.siemens.com/cax