

Data sheet

6GK1901-0DB40-6AA0

product type designation

product description

IE FC M12 Cable Connector PRO (PROFINET)

M12 connector with socket insert with high protection class, 8-pole, X-coded

IE FC M12 Cable Connector PRO 4x 2 M12 plug-in connectors that can be assembled in the field (X-coded) 8-pole; metal enclosure; FC quick-connect technology; female contact insert; 1 pack = 1 unit.



suitability for use

For connecting electrical cables to SCALANCE W (M12 gigabit interface) for fast assembly with the FastConnect system

transfer rate

transfer rate / for Industrial Ethernet

10 Mbit/s, 100 Mbit/s, 1000 Mbit/s, 10000 Mbit/s

interfaces

number of electrical connections

- for Industrial Ethernet FC TP cables
- for network components or terminal equipment

8
1

type of electrical connection

- for Industrial Ethernet FC TP cables

integrated cut-and-clamp contacts for 8-wire TP FC installation cable AWG24

- for network components or terminal equipment

M12 connector (X-coded)

type of electrical connection / FastConnect

Yes

mechanical data

material / of the enclosure

metal

locking mechanism design

Screwed joint

tightening torque / for M12 round connector / maximum

0.6 N·m

connector coding / of the M12 circular connector

X

design, dimensions and weights

type of cable outlet

180° cable outlet

width

16.8 mm

height

16.8 mm

depth

49 mm

net weight

40 g

connectable cable cross-section

6.5 ... 8 mm

connectable conductor cross-section

0.21 ... 0.33 mm²

ambient conditions

ambient temperature

-40 ... +85 °C

- during operation

-40 ... +85 °C

- during storage

-40 ... +85 °C

- during transport

resistant

chemical resistance

- to water

IP65/67

protection class IP

product features, product functions, product components / general

product feature

Yes

- PoE capability

Yes

- PoE+capability

• silicon-free	Yes
product component	Yes
• strain relief	
standards, specifications, approvals	
certificate of suitability	
• RoHS conformity	Yes
• UL approval	Yes
• cULus approval	Yes
• railway application in accordance with EN 50155	Yes
• fire protection in accordance with EN 45545-2	Yes
standard for structured cabling	Cat6A
further information / internet-Links	
Internet-Link	
• to web page: selection aid TIA Selection Tool	http://www.siemens.com/tia-selection-tool
• to website: Industrial communication	http://www.siemens.com/simatic-net
• to website: Industry Mall	https://mall.industry.siemens.com
• to website: Information and Download Center	http://www.siemens.com/industry/infocenter
• to website: Selection guide for cables and connectors	https://sie.ag/2QdIxcP
• to website: Image database	http://automation.siemens.com/bilddb
• to website: CAx-Download-Manager	http://www.siemens.com/cax
• to website: Industry Online Support	https://support.industry.siemens.com

last modified:

10/15/2022 