SIEMENS

Data sheet

6GK1901-1BB12-2AE0

product type designation	
product description	



IE FC RJ45 Plug 180 (4x2)

RJ45 data connector

Industrial Ethernet FastConnect RJ45 plug 180 4x 2, RJ45 plug-in connector; CAT6A; (10/100/1000/10000 Mbit/s) with rugged metal enclosure and FC connection system, for IE FC TP Cable 4x 2 (AWG24); 180° cable outlet 1 pack = 50 units.

suitability for use	For connection to IE FC TP cables 4x2, suitable for fast assembly with the FastConnect system
transfer rate	
transfer rate / for Industrial Ethernet	10 Mbit/s, 100 Mbit/s, 1000 Mbit/s, 10000 Mbit/s
interfaces	
number of electrical connections	
 for Industrial Ethernet FC TP cables 	1
 for network components or terminal equipment 	1
type of electrical connection	
for Industrial Ethernet FC TP cables	Integrated insulation-displacement contacts for 8-wire (AWG24) and 4- wire (AWG22) TP FC installation cables
 for network components or terminal equipment 	RJ45 connector
type of electrical connection / FastConnect	Yes
mechanical data	
material / of the enclosure	metal
number of reuses	10
locking mechanism design	other
design, dimensions and weights	
type of cable outlet	180° cable outlet
width	13.7 mm
height	16 mm
depth	55 mm
net weight	35 g
connectable cable cross-section	6.5 8 mm
connectable conductor cross-section	0.21 0.33 mm ²
ambient conditions	
ambient temperature	
 during operation 	-40 +85 °C
 during storage 	-40 +85 °C
 during transport 	-40 +85 °C
relative humidity	
 at 25 °C / without condensation / during operation / maximum 	95 %
protection class IP	IP20
product features, product functions, product components	/ general
product feature	
 PoE capability 	Yes
 PoE+capability 	Yes
silicon-free	Yes

Yes
Yes
Yes
Yes
No
Cat6A
http://www.siemens.com/tia-selection-tool
http://www.siemens.com/simatic-net
https://mall.industry.siemens.com
http://www.siemens.com/industry/infocenter
https://sie.ag/2QdlxcP
http://automation.siemens.com/bilddb
http://www.siemens.com/cax
https://support.industry.siemens.com

last modified:

7/7/2022 🖸