SIEMENS

Data sheet

Product type designation Product description

PB M12 connector

M12 connector with pin insert, 5-pole, B-coded M12 CONNECTING PLUG FOR ET200 WITH AXIAL CABLE OUTLET FOR FIELD ASSEMBLY PIN CONNECTOR, PACK. UNIT 5 PIECES



Figure similar

Suitability for use	For connecting electrical PB bus cables to ET200
Transmission rate	
Transfer rate / with PROFIBUS	9.6 kbit/s 12 Mbit/s
Interfaces	
Number of electrical connections	
 for PROFIBUS cables 	1
 for network components or terminal equipment 	1
Type of electrical connection	
 for PROFIBUS cables 	Integrated screw-type contacts for 2-core PB installation cables
 for network components or terminal equipment 	M12 connector (male insert, 4-pin, B-coded)
Type of electrical connection / FastConnect	No
Mechanical data	
Material / of the enclosure	metal
Locking mechanism design	Screw

Design, dimensions and weight		
Type of cable outlet	180° cable outlet	
Width	19 mm	
Height	19 mm	
Depth	73 mm	
Net weight	40 g	
Permitted ambient conditions		
Ambient temperature		
 during operation 	-40 +70 °C	
 during storage 	-40 +80 °C	
• during transport	-40 +80 °C	
Chemical resistance / to water	resistant	
Protection class IP	IP65/67	
Product properties, functions, components / general		
Product feature		
• silicon-free	Yes	
Product component		
• strain relief	Yes	
Standards, specifications, approvals		
Certificate of suitability		
 RoHS conformity 	Yes	
 UL approval 	No	
 Railway application in accordance with EN 	No	
50155		
Further Information / Internet Links		
Internet-Link		
to website: Selector SIMATIC NET SELECTION TOOL	http://www.siemens.com/snst	
• to website: Industrial communication	http://www.siemens.com/simatic-net	
• to website: Industry Mall	https://mall.industry.siemens.com	
• to website: Information and Download Center	http://www.siemens.com/industry/infocenter	
• to website: Image database	http://automation.siemens.com/bilddb	
• to website: CAx Download Manager	http://www.siemens.com/cax	
• to website: Industry Online Support	https://support.industry.siemens.com	
last modified:	07/07/2016	