

product type designation

product description



PB FC M12 Cable Connector PRO

M12 connector with socket insert, 5-pole, B-coded

PROFIBUS FC M12 Cable connector PRO, M12 plug-in connector with rugged metal enclosure and FC connection system, with axial cable outlet, for use with ET 200 PRO, female contact insert (B-coded) 1 pack=5 units.

suitability for use

For connecting electrical PB FC bus cables to ET200 PRO, suitable for fast assembly with the FastConnect system

transfer rate

transfer rate / with PROFIBUS

9.6 kbit/s ... 12 Mbit/s

interfaces

number of electrical connections

- for PROFIBUS cables
- for network components or terminal equipment

1

1

type of electrical connection

- for PROFIBUS cables
- for network components or terminal equipment

Integrated insulation displacement contacts for 2-core PB FC installation cables

M12 connector (female insert, 5-pin, B-coded)

type of electrical connection / FastConnect

Yes

mechanical data

material / of the enclosure

metal

number of reuses

10

locking mechanism design

Screwed joint

tightening torque / for M12 round connector / maximum

0.6 N·m

connector coding / of the M12 circular connector

B

design, dimensions and weights

type of cable outlet

180° cable outlet

width

19 mm

height

19 mm

depth

73 mm

net weight

40 g

connectable cable cross-section

6 ... 8 mm

connectable conductor cross-section

0.33 mm²

ambient conditions

ambient temperature

- during operation
- during storage
- during transport

-40 ... +85 °C

-40 ... +85 °C

-40 ... +85 °C

chemical resistance

- to water

resistant

protection class IP

IP65/67

product features, product functions, product components / general

product feature

- silicon-free

Yes

product component

<ul style="list-style-type: none"> • strain relief 	Yes
standards, specifications, approvals	
certificate of suitability	
<ul style="list-style-type: none"> • RoHS conformity 	Yes
<ul style="list-style-type: none"> • UL approval 	Yes
<ul style="list-style-type: none"> • cULus approval 	Yes
<ul style="list-style-type: none"> • railway application in accordance with EN 50155 	No
further information / internet-Links	
Internet-Link	
<ul style="list-style-type: none"> • to web page: selection aid TIA Selection Tool 	http://www.siemens.com/tia-selection-tool
<ul style="list-style-type: none"> • to website: Industrial communication 	http://www.siemens.com/simatic-net
<ul style="list-style-type: none"> • to website: Industry Mall 	https://mall.industry.siemens.com
<ul style="list-style-type: none"> • to website: Information and Download Center 	http://www.siemens.com/industry/infocenter
<ul style="list-style-type: none"> • to website: Selection guide for cables and connectors 	https://sie.ag/2QdlxcP
<ul style="list-style-type: none"> • to website: Image database 	http://automation.siemens.com/bilddb
<ul style="list-style-type: none"> • to website: CAx-Download-Manager 	http://www.siemens.com/cax
<ul style="list-style-type: none"> • to website: Industry Online Support 	https://support.industry.siemens.com
last modified:	10/15/2022 