



SCALANCE X206-1, managed IE switch, 6x 10/100 Mbit/s RJ45 ports, 1x 100 Mbit/s multimode BFOC, LED diagnostics, error signaling contact with set pushbutton, redundant power supply, PROFINET IO device, network management, redundancy manager integrated, incl. electron. manual on CD-ROM, C-PLUG optional.

<b>product type designation</b>	<b>SCALANCE X206-1</b>
<b>transfer rate</b>	
transfer rate	10 Mbit/s, 100 Mbit/s
<b>interfaces / for communication / integrated</b>	
number of electrical connections	6
<ul style="list-style-type: none"> <li>for network components or terminal equipment</li> </ul>	6
number of 10/100 Mbit/s RJ45 ports / integrated	6
<ul style="list-style-type: none"> <li>with securing collar</li> </ul>	6
number of 100 Mbit/s ST(BFOC) ports	1
<ul style="list-style-type: none"> <li>for multimode</li> </ul>	1
<b>interfaces / other</b>	
number of electrical connections	1
<ul style="list-style-type: none"> <li>for signaling contact</li> </ul>	1
<ul style="list-style-type: none"> <li>for power supply</li> </ul>	1
type of electrical connection	2-pole terminal block
<ul style="list-style-type: none"> <li>for signaling contact</li> </ul>	4-pole terminal block
<ul style="list-style-type: none"> <li>for power supply</li> </ul>	4-pole terminal block
design of the removable storage	Yes
<ul style="list-style-type: none"> <li>C-PLUG</li> </ul>	Yes
<b>signal inputs/outputs</b>	
operating voltage / of the signaling contacts	24 V
<ul style="list-style-type: none"> <li>at DC / rated value</li> </ul>	24 V
operational current / of the signaling contacts	0.1 A
<ul style="list-style-type: none"> <li>at DC / maximum</li> </ul>	0.1 A
<b>supply voltage, current consumption, power loss</b>	
product component / connection for redundant voltage supply	Yes
<b>type of voltage / 1 / of the supply voltage</b>	DC
<ul style="list-style-type: none"> <li>supply voltage / 1 / rated value</li> </ul>	24 V
<ul style="list-style-type: none"> <li>power loss [W] / 1 / rated value</li> </ul>	5.28 W
<ul style="list-style-type: none"> <li>supply voltage / 1 / rated value</li> </ul>	18 ... 32 V
<ul style="list-style-type: none"> <li>consumed current / 1 / maximum</li> </ul>	0.22 A
<ul style="list-style-type: none"> <li>type of electrical connection / 1 / for power supply</li> </ul>	4-pole terminal block
<ul style="list-style-type: none"> <li>product component / 1 / fusing at power supply input</li> </ul>	Yes
<ul style="list-style-type: none"> <li>fuse protection type / 1 / at input for supply voltage</li> </ul>	0.6 A / 60 V
<b>ambient conditions</b>	
ambient temperature	-40 ... +60 °C
<ul style="list-style-type: none"> <li>during operation</li> </ul>	-40 ... +60 °C
<ul style="list-style-type: none"> <li>during storage</li> </ul>	-40 ... +70 °C
<ul style="list-style-type: none"> <li>during transport</li> </ul>	-40 ... +70 °C
relative humidity	

<ul style="list-style-type: none"> <li>• at 25 °C / without condensation / during operation / maximum</li> </ul>	95 %
protection class IP	IP30
<b>design, dimensions and weights</b>	
design	compact
width	60 mm
height	125 mm
depth	124 mm
net weight	0.78 kg
fastening method	
<ul style="list-style-type: none"> <li>• 35 mm top hat DIN rail mounting</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• wall mounting</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• S7-300 rail mounting</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• S7-1500 rail mounting</li> </ul>	No
<b>product features, product functions, product components / general</b>	
cascading in the case of a redundant ring / at reconfiguration time of <~0.3~s	100
cascading in cases of star topology	any (depending only on signal propagation time)
<b>product functions / management, configuration, engineering</b>	
product function	
<ul style="list-style-type: none"> <li>• CLI</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• web-based management</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• MIB support</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• TRAPs via email</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• configuration with STEP 7</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• port mirroring</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• multiport mirroring</li> </ul>	No
<ul style="list-style-type: none"> <li>• with IRT / PROFINET IO switch</li> </ul>	No
<ul style="list-style-type: none"> <li>• PROFINET IO diagnosis</li> </ul>	Yes
PROFINET conformity class	B
product function / switch-managed	Yes
protocol / is supported	
<ul style="list-style-type: none"> <li>• Telnet</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• HTTP</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• HTTPS</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• TFTP</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• FTP</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• BOOTP</li> </ul>	No
<ul style="list-style-type: none"> <li>• DCP</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• LLDP</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• SNMP v1</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• SNMP v2</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• SNMP v3</li> </ul>	Yes
identification & maintenance function	
<ul style="list-style-type: none"> <li>• I&amp;M0 - device-specific information</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• I&amp;M1 – higher level designation/location designation</li> </ul>	Yes
<b>product functions / diagnostics</b>	
product function	
<ul style="list-style-type: none"> <li>• port diagnostics</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• statistics Packet Size</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• statistics packet type</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• error statistics</li> </ul>	Yes
<b>product functions / DHCP</b>	
product function	
<ul style="list-style-type: none"> <li>• DHCP client</li> </ul>	Yes
<b>product functions / redundancy</b>	
product function	
<ul style="list-style-type: none"> <li>• ring redundancy</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• High Speed Redundancy Protocol (HRP)</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• high speed redundancy protocol (HRP) with redundancy manager</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• high speed redundancy protocol (HRP) with standby redundancy</li> </ul>	No

protocol / is supported / Media Redundancy Protocol (MRP)	Yes
product function	
• media redundancy protocol (MRP) with redundancy manager	Yes
• Parallel Redundancy Protocol (PRP)/operation in the PRP-network	Yes
• Parallel Redundancy Protocol (PRP)/Redundant Network Access (RNA)	No
• passive listening	Yes
<b>product functions / security</b>	
protocol / is supported	
• SSH	Yes
<b>product functions / time</b>	
product function	
• SICLOCK support	Yes
protocol / is supported	
• NTP	No
• SNTP	Yes
<b>standards, specifications, approvals</b>	
standard	
• for emitted interference	EN 61000-6-4:2001 (Class A)
• for interference immunity	EN 61000-6-2:2001
MTBF	78.71 a
reference code	
• according to IEC 81346-2	KF
• according to IEC 81346-2:2019	KFE
<b>standards, specifications, approvals / CE</b>	
certificate of suitability / CE marking	Yes
<b>standards, specifications, approvals / hazardous environments</b>	
standard / for hazardous zone	EN 60079-0: 2006, EN60079-15: 2005, II 3 (2) G Ex nA [op is] IIC T4, KEMA 07 ATEX 0145 X
certificate of suitability	
• CCC / for hazardous zone according to GB standard	Yes
• for cULus HazLoc / as File Nr.	E240480 (NWHP, NWHP7)
<b>standards, specifications, approvals / other</b>	
certificate of suitability	EN 61000-6-2:2001, EN 61000-6-4:2001
• C-Tick	Yes
• KC approval	Yes
• railway application in accordance with EN 50155	No
• railway application in accordance with EN 50124-1	No
<b>standards, specifications, approvals / marine classification</b>	
Marine classification association	
• American Bureau of Shipping Europe Ltd. (ABS)	Yes
• French marine classification society (BV)	Yes
• Det Norske Veritas (DNV)	Yes
• Germanische Lloyd (GL)	Yes
• Lloyds Register of Shipping (LRS)	Yes
• Nippon Kaiji Kyokai (NK)	Yes
• Polski Rejestr Statkow (PRS)	Yes
• Royal Institution of Naval Architects (RINA)	No
<b>further information / internet-Links</b>	
Internet-Link	
• to web page: selection aid TIA Selection Tool	<a href="http://www.siemens.com/tia-selection-tool">http://www.siemens.com/tia-selection-tool</a>
• to website: Industrial communication	<a href="http://www.siemens.com/simatic-net">http://www.siemens.com/simatic-net</a>
• to website: Industry Mall	<a href="https://mall.industry.siemens.com">https://mall.industry.siemens.com</a>
• to website: Information and Download Center	<a href="http://www.siemens.com/industry/infocenter">http://www.siemens.com/industry/infocenter</a>
• to website: Image database	<a href="http://automation.siemens.com/bilddb">http://automation.siemens.com/bilddb</a>
• to website: CAX-Download-Manager	<a href="http://www.siemens.com/cax">http://www.siemens.com/cax</a>
• to website: Industry Online Support	<a href="https://support.industry.siemens.com">https://support.industry.siemens.com</a>
<b>security information</b>	
security information	Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions.

machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action (e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit <http://www.siemens.com/industrialsecurity>. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit <http://support.automation.siemens.com>. (V3.4)

last modified:

9/16/2022 