



SCALANCE XB213-3 managed Layer 2 IE switch 13x 10/100 Mbit/s RJ45 ports, 3x MM FO SC-port 1x console port, diagnostics LED, redundant power supply, IEC 62443-4-2 certified; temperature range 0 °C to +60 °C; DIN-rail mounting; default PROFINET.

product type designation	SCALANCE XB213-3
transfer rate	
transfer rate	10 Mbit/s, 100 Mbit/s
number of ports / maximum	16
interfaces / for communication / maximum configuration for modular devices	
number of electrical ports / maximum	13
number of optical ports / maximum	3
interfaces / for communication / integrated	
number of electrical connections <ul style="list-style-type: none">for network components or terminal equipment	13; RJ45
number of 100 Mbit/s SC ports <ul style="list-style-type: none">for multimode	3
interfaces / other	
number of electrical connections <ul style="list-style-type: none">for operator consolefor management purposesfor power supply	1 1 1
type of electrical connection <ul style="list-style-type: none">for operator consolefor management purposes	RJ11 RJ45
supply voltage, current consumption, power loss	
product component / connection for redundant voltage supply	Yes
type of voltage / 1 / of the supply voltage <ul style="list-style-type: none">supply voltage / 1 / rated valuepower loss [W] / 1 / rated valuesupply voltage / 1 / rated valueconsumed current / 1 / maximumtype of electrical connection / 1 / for power supplyproduct component / 1 / fusing at power supply input	DC 24 V 9.8 W 19.2 ... 28.8 V 0.41 A 6-pole terminal block Yes
ambient conditions	
ambient temperature <ul style="list-style-type: none">during operationduring storageduring transport	0 ... 60 °C -40 ... +70 °C -40 ... +70 °C
relative humidity <ul style="list-style-type: none">at 25 °C / without condensation / during operation / maximum	95 %
protection class IP	IP20
design, dimensions and weights	
design	Box

width	120 mm
height	117 mm
depth	109 mm
net weight	0.5 kg
material / of the enclosure	Plastic
fastening method	
• 35 mm top hat DIN rail mounting	Yes

product features, product functions, product components / general

cascading in the case of a redundant ring / at reconfiguration time of <~0.3~s	50
cascading in cases of star topology	any (depending only on signal propagation time)

product functions / management, configuration, engineering

product function	
• CLI	Yes
• web-based management	Yes
• MIB support	Yes
• TRAPs via email	Yes
• configuration with STEP 7	Yes
• RMON	Yes
• port mirroring	Yes
• multiport mirroring	No
• CoS	Yes
• PROFINET IO diagnosis	Yes
PROFINET conformity class	B
product function / switch-managed	Yes
telegram length / for Ethernet / maximum	1522 byte
protocol / is supported	
• Telnet	Yes
• HTTP	Yes
• HTTPS	Yes
• TFTP	Yes
• FTP	Yes
• DCP	Yes
• LLDP	Yes
• EtherNet/IP	Yes
• SNMP v1	Yes
• SNMP v2	Yes
• SNMP v3	Yes
• IGMP (snooping/querier)	Yes
identification & maintenance function	
• I&M0 - device-specific information	Yes
• I&M1 - higher level designation/location designation	Yes

product functions / diagnostics

product function	
• port diagnostics	Yes
• statistics Packet Size	Yes
• statistics packet type	Yes
• error statistics	Yes
• SysLog	Yes
• loopback diagnostics	Yes

product functions / VLAN

product function	
• VLAN - port based	Yes

product functions / DHCP

product function	
• DHCP client	Yes

product functions / redundancy

product function	
• ring redundancy	Yes
• High Speed Redundancy Protocol (HRP)	Yes
• high speed redundancy protocol (HRP) with redundancy manager	Yes
• high speed redundancy protocol (HRP) with standby	Yes

redundancy protocol / is supported / Media Redundancy Protocol (MRP) product function <ul style="list-style-type: none"> media redundancy protocol (MRP) with redundancy manager Media Redundancy Protocol Interconnection (MRP-I) redundancy procedure STP redundancy procedure RSTP redundancy procedure RSTP+ Parallel Redundancy Protocol (PRP)/operation in the PRP-network passive listening protocol / is supported <ul style="list-style-type: none"> LACP 	Yes Yes Yes Yes Yes No Yes Yes
product functions / security	
product function <ul style="list-style-type: none"> ACL - MAC-based ACL - port/MAC-based IEEE 802.1x (radius) broadcast/multicast/unicast limiter broadcast blocking protocol / is supported <ul style="list-style-type: none"> SSH SSL 	Yes Yes Yes Yes Yes Yes Yes
product functions / time	
product function <ul style="list-style-type: none"> SICLOCK support NTP-client SNTP client protocol / is supported <ul style="list-style-type: none"> SNTP 	Yes Yes Yes Yes
standards, specifications, approvals	
standard <ul style="list-style-type: none"> for emitted interference for interference immunity IT security for industrial automation systems / according to IEC 62443-4-2:2019 reference code <ul style="list-style-type: none"> according to IEC 81346-2 according to IEC 81346-2:2019 	EN 61000-6-4 (Class A) EN 61000-6-2 Yes KF KFE
standards, specifications, approvals / CE	
certificate of suitability / CE marking certificate of suitability / RoHS conformity	Yes Yes; 2011/65/EU
standards, specifications, approvals / hazardous environments	
standard / for hazardous zone certificate of suitability <ul style="list-style-type: none"> CCC / for hazardous zone according to GB standard 	EN 60079-0 : 2006, EN 60079-15: 2005, II 3 G Ex nA II T4 KEMA 07 ATEX 0145X Yes
standards, specifications, approvals / other	
certificate of suitability <ul style="list-style-type: none"> C-Tick KC approval 	EN 61000-6-2, EN 61000-6-4 Yes Yes
further information / internet-Links	
Internet-Link <ul style="list-style-type: none"> to web page: selection aid TIA Selection Tool to website: Industrial communication to website: Industry Mall to website: Information and Download Center to website: Image database to website: CAx-Download-Manager to website: Industry Online Support 	http://www.siemens.com/tia-selection-tool http://www.siemens.com/simatic-net https://mall.industry.siemens.com http://www.siemens.com/industry/infocenter http://automation.siemens.com/bilddb http://www.siemens.com/cax https://support.industry.siemens.com

security information

security information

Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action(e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit <http://www.siemens.com/industrialsecurity>. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit <http://support.automation.siemens.com>. (V3.4)

last modified:

2/7/2023 