

\*\*\*\*\* spare part \*\*\*\*\* SCALANCE XR324-4M EEC; managed IE switch, 19 rack; 16x 10/100/1000 Mbit/s for RJ45 ports electrical; 4x 100/1000 Mbit/s for 2-port media modules, electrical or optical; LED diagnostics; error signaling contact; select/set pushbutton, PROFINET IO device, network management, integrated redundancy manager; power supply 2x 24 V DC; ports at the back.



<b>product type designation</b>	<b>SCALANCE XR324-4M EEC</b>
<b>transfer rate</b>	
transfer rate	10 Mbit/s, 100 Mbit/s, 1000 Mbit/s
<b>interfaces / for communication / integrated</b>	
number of electrical connections	16; RJ45
<ul style="list-style-type: none"> <li>for network components or terminal equipment</li> </ul>	
number of 100 Mbit/s ST(BFOC) ports	8
<ul style="list-style-type: none"> <li>for multimode</li> </ul>	
number of 100 Mbit/s SC ports	8
<ul style="list-style-type: none"> <li>for multimode</li> </ul>	
number of 1000 Mbit/s LC ports	8
<ul style="list-style-type: none"> <li>for multimode</li> <li>for single mode (LD)</li> </ul>	8
<b>interfaces / other</b>	
number of electrical connections	1
<ul style="list-style-type: none"> <li>for operator console</li> <li>for signaling contact</li> <li>for media module</li> <li>for power supply</li> </ul>	1 1 4 2
type of electrical connection	RJ11
<ul style="list-style-type: none"> <li>for operator console</li> <li>for signaling contact</li> <li>for power supply</li> </ul>	2 x 2-pole terminal block 2 x 4-pole terminal block
design of the removable storage	Yes
<ul style="list-style-type: none"> <li>C-PLUG</li> </ul>	
<b>signal inputs/outputs</b>	
operating voltage / of the signaling contacts	24 V
<ul style="list-style-type: none"> <li>at DC / rated value</li> </ul>	
operational current / of the signaling contacts	0.1 A
<ul style="list-style-type: none"> <li>at DC / maximum</li> </ul>	
<b>supply voltage, current consumption, power loss</b>	
product component / connection for redundant voltage supply	Yes
type of voltage supply / redundant power supply unit	Yes
<b>type of voltage / 1 / of the supply voltage</b>	DC
<ul style="list-style-type: none"> <li>supply voltage / 1 / rated value</li> <li>power loss [W] / 1 / rated value</li> <li>supply voltage / 1 / rated value</li> <li>consumed current / 1 / maximum</li> <li>type of electrical connection / 1 / for power supply</li> <li>product component / 1 / fusing at power supply input</li> </ul>	24 V 40 W 19.2 ... 57.6 V 1.6 A 2 x 4-pole terminal block Yes

## ambient conditions

ambient temperature	
• during operation	-40 ... +70 °C
• during storage	-40 ... +85 °C
• during transport	-40 ... +85 °C
• note	Extended temperature upper limit of +85° C permitted for 16 hours. Reduced operating temperature through the use of media modules (-40 °C to +70 °C) or SFP plug-in transceivers (-40 °C to +60 °C)
relative humidity	
• at 25 °C / without condensation / during operation / maximum	95 %
protection class IP	IP20

## design, dimensions and weights

design	19" rack
number of modular height units / relating to 19-inch cabinet	1
width	483 mm
height	44 mm
depth	305 mm
net weight	6.8 kg
fastening method	When used in shipbuilding, the device must be secured in the 19" rack at four points
• 19-inch installation	Yes
• 35 mm top hat DIN rail mounting	No
• wall mounting	No
• S7-300 rail mounting	No
• S7-1500 rail mounting	No

## product features, product functions, product components / general

cascading in the case of a redundant ring / at reconfiguration time of <1~0.3~s	100
cascading in cases of star topology	any (depending only on signal propagation time)

## product functions / management, configuration, engineering

product function	
• CLI	Yes
• web-based management	Yes
• MIB support	Yes
• TRAPs via email	Yes
• configuration with STEP 7	Yes
• RMON	Yes
• port mirroring	Yes
• multiport mirroring	Yes
• CoS	Yes
• PROFINET IO diagnosis	Yes
PROFINET conformity class	B
product function / switch-managed	Yes
protocol / is supported	
• Telnet	Yes
• HTTP	Yes
• HTTPS	Yes
• TFTP	Yes
• FTP	Yes
• BOOTP	Yes
• GMRP	Yes
• DCP	Yes
• LLDP	Yes
• SNMP v1	Yes
• SNMP v2	Yes
• SNMP v3	Yes
• IGMP (snooping/querier)	Yes
identification & maintenance function	
• I&M0 - device-specific information	Yes
• I&M1 - higher level designation/location designation	Yes

## product functions / diagnostics

product function	
------------------	--

• port diagnostics	Yes
• statistics Packet Size	Yes
• statistics packet type	Yes
• error statistics	Yes
• SysLog	Yes

#### product functions / VLAN

product function	
• VLAN - port based	Yes
• VLAN - protocol-based	No
• VLAN - IP-based	No
• VLAN dynamic	Yes
number of VLANs / maximum	255
number of VLANs - dynamic / maximum	255
protocol / is supported / GVRP	Yes

#### product functions / DHCP

product function	
• DHCP client	Yes
• DHCP Option 82	Yes
• DHCP Option 66	Yes
• DHCP Option 67	Yes

#### product functions / redundancy

product function	
• ring redundancy	Yes
• High Speed Redundancy Protocol (HRP)	Yes
• high speed redundancy protocol (HRP) with redundancy manager	Yes
• high speed redundancy protocol (HRP) with standby redundancy	Yes
protocol / is supported / Media Redundancy Protocol (MRP)	Yes
product function	
• media redundancy protocol (MRP) with redundancy manager	Yes
• redundancy procedure STP	Yes
• redundancy procedure RSTP	Yes
• redundancy procedure MSTP	Yes
• Parallel Redundancy Protocol (PRP)/operation in the PRP-network	Yes
• Parallel Redundancy Protocol (PRP)/Redundant Network Access (RNA)	No
• passive listening	Yes
protocol / is supported	
• STP/RSTP	Yes
• STP	Yes
• RSTP	Yes
• MSTP	Yes
• RSTP big network support	Yes
• LACP	Yes

#### product functions / security

product function	
• ACL - MAC-based	Yes
• ACL - port/MAC-based	Yes
• IEEE 802.1x (radius)	Yes
• broadcast/multicast/unicast limiter	Yes
• broadcast blocking	Yes
protocol / is supported	
• SSH	Yes

#### product functions / time

product function	
• SICLOCK support	Yes
protocol / is supported	
• NTP	Yes
• SNTP	Yes
• IEEE 1588 profile default	Yes

standards, specifications, approvals	
standard <ul style="list-style-type: none"> <li>• for FM</li> <li>• for safety / from CSA and UL</li> <li>• for emitted interference</li> <li>• for interference immunity</li> </ul> MTBF reference code <ul style="list-style-type: none"> <li>• according to IEC 81346-2</li> <li>• according to IEC 81346-2:2019</li> </ul>	FM3611: Class 1, Division 2, Group A, B, C, D / T4, Class 1, Zone 2, Group IIC, T4 UL 60950-1, CSA C22.2 No. 60950-1-03 EN 61000-6-4:2007 (Class A) EN 61000-6-2:2005 20 a KF KFE
standards, specifications, approvals / CE	
certificate of suitability / CE marking standard <ul style="list-style-type: none"> <li>• for EMC</li> </ul>	Yes IEC 61850, IEEE 1613
standards, specifications, approvals / hazardous environments	
standard / for hazardous zone <ul style="list-style-type: none"> <li>• from CSA and UL</li> </ul>	EN 60079-0 : 2006, EN 60079-15: 2005, II 3 G Ex nA II T4 KEMA 07 ATEX 0145X ANSI / ISA 12.12.01, CSA C22.2 No. 142-M1987, CL. 1 / Div. 2 / GP. A, B, C, D T4, CL. 1 / Zone 2 / GP. IIC, T4
standards, specifications, approvals / other	
certificate of suitability <ul style="list-style-type: none"> <li>• C-Tick</li> <li>• KC approval</li> <li>• IEC 61850-3</li> </ul>	EN 61000-6-2:2005, EN 61000-6-4:2007 Yes Yes Yes
standards, specifications, approvals / marine classification	
Marine classification association <ul style="list-style-type: none"> <li>• American Bureau of Shipping Europe Ltd. (ABS)</li> <li>• French marine classification society (BV)</li> <li>• Det Norske Veritas (DNV)</li> <li>• Germanische Lloyd (GL)</li> <li>• DNV GL</li> <li>• Lloyds Register of Shipping (LRS)</li> <li>• Nippon Kaiji Kyokai (NK)</li> <li>• Polski Rejestr Statkow (PRS)</li> <li>• Royal Institution of Naval Architects (RINA)</li> </ul>	Yes Yes No No Yes Yes Yes No Yes
further information / internet-Links	
Internet-Link <ul style="list-style-type: none"> <li>• to web page: selection aid TIA Selection Tool</li> <li>• to website: Industrial communication</li> <li>• to website: Industry Mall</li> <li>• to website: Information and Download Center</li> <li>• to website: Image database</li> <li>• to website: CAx-Download-Manager</li> <li>• to website: Industry Online Support</li> </ul>	<a href="http://www.siemens.com/tia-selection-tool">http://www.siemens.com/tia-selection-tool</a> <a href="http://www.siemens.com/simatic-net">http://www.siemens.com/simatic-net</a> <a href="https://mall.industry.siemens.com">https://mall.industry.siemens.com</a> <a href="http://www.siemens.com/industry/infocenter">http://www.siemens.com/industry/infocenter</a> <a href="http://automation.siemens.com/bilddb">http://automation.siemens.com/bilddb</a> <a href="http://www.siemens.com/cax">http://www.siemens.com/cax</a> <a href="https://support.industry.siemens.com">https://support.industry.siemens.com</a>
security information	
security information	Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action (e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit <a href="http://www.siemens.com/industrialsecurity">http://www.siemens.com/industrialsecurity</a> . To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit <a href="http://support.automation.siemens.com">http://support.automation.siemens.com</a> . (V3.4)

last modified:

9/17/2022 