

***** spare part ***** SCALANCE XR324-4M PoE TS; managed IE switch, 19 rack; 8x 10/100/1000 Mbit/s for RJ45 ports electrical with PoE, 8x 10/100/1000 Mbit/s for RJ45 ports electrical without PoE; 4x 10/100/1000 Mbit/s 2-port media modules, electrical or optical; LED diagnostics; error signaling contact; select/set pushbutton, PROFINET IO device, power supply 24 V DC; Ports in the front.



product type designation	SCALANCE XR324-4M PoE TS
transfer rate	
transfer rate	10 Mbit/s, 100 Mbit/s, 1000 Mbit/s
interfaces / for communication / integrated	
number of electrical connections	16; RJ45
<ul style="list-style-type: none"> for network components or terminal equipment for Power-over-Ethernet / for network components or terminal equipment 	8
number of 100 Mbit/s ST(BFOC) ports	8
<ul style="list-style-type: none"> for multimode 	8
number of 100 Mbit/s SC ports	8
<ul style="list-style-type: none"> for multimode 	8
number of 1000 Mbit/s LC ports	8
<ul style="list-style-type: none"> for multimode for single mode (LD) 	8
interfaces / other	
number of electrical connections	1
<ul style="list-style-type: none"> for operator console for signaling contact for media module for power supply 	1 1 4 1
type of electrical connection	RJ11
<ul style="list-style-type: none"> for operator console for signaling contact for power supply 	2-pole terminal block 4-pole terminal block
design of the removable storage	Yes
<ul style="list-style-type: none"> C-PLUG 	Yes
signal inputs/outputs	
operating voltage / of the signaling contacts	24 V
<ul style="list-style-type: none"> at DC / rated value 	24 V
operational current / of the signaling contacts	0.1 A
<ul style="list-style-type: none"> at DC / maximum 	0.1 A
supply voltage, current consumption, power loss	
type of voltage supply / redundant power supply unit	No
type of voltage / 1 / of the supply voltage	DC
<ul style="list-style-type: none"> supply voltage / 1 / rated value power loss [W] / 1 / rated value supply voltage / 1 / rated value consumed current / 1 / maximum type of electrical connection / 1 / for power supply product component / 1 / fusing at power supply input 	24 V 46 W 19.2 ... 28.8 V 4.2 A 4-pole terminal block Yes

- port diagnostics Yes
- statistics Packet Size Yes
- statistics packet type Yes
- error statistics Yes
- SysLog Yes

product functions / VLAN

- product function
 - VLAN - port based Yes
 - VLAN - protocol-based No
 - VLAN - IP-based No
 - VLAN dynamic Yes
- number of VLANs / maximum 255
- number of VLANs - dynamic / maximum 255
- protocol / is supported / GVRP Yes

product functions / DHCP

- product function
 - DHCP client Yes
 - DHCP Option 82 Yes
 - DHCP Option 66 Yes
 - DHCP Option 67 Yes

product functions / redundancy

- product function
 - ring redundancy Yes
 - High Speed Redundancy Protocol (HRP) Yes
 - high speed redundancy protocol (HRP) with redundancy manager Yes
 - high speed redundancy protocol (HRP) with standby redundancy Yes
- protocol / is supported / Media Redundancy Protocol (MRP) Yes
- product function
 - media redundancy protocol (MRP) with redundancy manager Yes
 - redundancy procedure STP Yes
 - redundancy procedure RSTP Yes
 - redundancy procedure MSTP Yes
 - passive listening Yes
- protocol / is supported
 - STP/RSTP Yes
 - STP Yes
 - RSTP Yes
 - MSTP Yes
 - RSTP big network support Yes
 - LACP Yes

product functions / security

- product function
 - ACL - MAC-based Yes
 - ACL - port/MAC-based Yes
 - IEEE 802.1x (radius) Yes
 - broadcast/multicast/unicast limiter Yes
 - broadcast blocking Yes
- protocol / is supported
 - SSH Yes

product functions / time

- product function
 - SICLOCK support Yes
- protocol / is supported
 - NTP Yes
 - SNTP Yes
 - IEEE 1588 profile default Yes

standards, specifications, approvals

- standard
 - for FM FM3611: Class 1, Divison 2, Group A, B, C, D / T4, Class 1, Zone 2,

<ul style="list-style-type: none"> • for safety / from CSA and UL • for emitted interference • for interference immunity 	Group IIC, T4 UL 60950-1, CSA C22.2 No. 60950-1 EN 61000-6-4:2007 (Class A) EN 61000-6-2:2006
reference code	KF
<ul style="list-style-type: none"> • according to IEC 81346-2 • according to IEC 81346-2:2019 	KFE
standards, specifications, approvals / CE	
certificate of suitability / CE marking	Yes
standards, specifications, approvals / hazardous environments	
standard / for hazardous zone	EN 60079-0 : 2006, EN 60079-15: 2005, II 3 G Ex nA II T4 KEMA 07 ATEX 0145X
<ul style="list-style-type: none"> • from CSA and UL 	UL 1604 and UL 2279-15 (Hazardous Location), CSA C22.2 No. 213-M1987, Class 1 / Division 2 / Group A, B, C, D / T4, Class 1 / Zone 2 / Group IIC / T4
standards, specifications, approvals / other	
certificate of suitability	EN 61000-6-2:2006, EN 61000-6-4:2007
<ul style="list-style-type: none"> • C-Tick 	Yes
<ul style="list-style-type: none"> • KC approval 	Yes
<ul style="list-style-type: none"> • railway application in accordance with EN 50155 	Yes
<ul style="list-style-type: none"> • railway application in accordance with EN 50121-4 	Yes
further information / internet-Links	
Internet-Link	
<ul style="list-style-type: none"> • to web page: selection aid TIA Selection Tool • to website: Industrial communication • to website: Industry Mall • to website: Information and Download Center • to website: Image database • to website: CAX-Download-Manager • to website: Industry Online Support 	http://www.siemens.com/tia-selection-tool http://www.siemens.com/simatic-net https://mall.industry.siemens.com http://www.siemens.com/industry/infocenter http://automation.siemens.com/bilddb http://www.siemens.com/cax https://support.industry.siemens.com
security information	
security information	<p>Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action (e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit http://www.siemens.com/industrialsecurity. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit http://support.automation.siemens.com. (V3.4)</p>

last modified:

9/17/2022 