## 6GK5408-0PA00-8AP2



product type designation



PE408PoE Port Extender for SCALANCE XM-400 managed modular IE switch; extension by 8x 10/100/1000 Mbit/s RJ45 with up to 8 ports PoE according to IEEE802.3AT; for PoE separate power supply required.

product type designation	SCALANCE FE400FUE
transfer rate	
transfer rate	10 Mbit/s, 100 Mbit/s, 1000 Mbit/s
interfaces / for communication / maximum configuration for mo	dular devices
number of electrical ports / maximum	8
number of electrical ports / with PoE / maximum	8
interfaces / for communication / integrated	
number of electrical connections	
<ul> <li>for network components or terminal equipment</li> </ul>	8
<ul> <li>for Power-over-Ethernet / for network components or terminal equipment</li> </ul>	8
number of 10/100/1000 Mbit/s RJ45 ports / integrated	
<ul><li>with securing collar / with PoE</li></ul>	8
interfaces / other	
type of electrical connection	
<ul><li>for power supply</li></ul>	2-pole terminal block
number of extender expansion interfaces	2
product feature / hot-swappable interface modules	Yes
supply voltage, current consumption, power loss	
product component / connection for redundant voltage supply	Yes
supplied active power / of PSE / with PoE	
• per port / maximum	30 W
total / maximum	180 W
type of voltage / 1 / of the supply voltage	DC
<ul> <li>supply voltage / 1 / rated value</li> </ul>	54 V
<ul><li>power loss [W] / 1 / rated value</li></ul>	4.8 W
<ul><li>supply voltage / 1 / rated value</li></ul>	51.3 56.7 V
<ul><li>consumed current / 1 / maximum</li></ul>	0.2 A
<ul> <li>type of electrical connection / 1 / for power supply</li> </ul>	2-pole terminal block
<ul> <li>product component / 1 / fusing at power supply input</li> </ul>	Yes
fuse protection type / 1 / at input for supply voltage	F 4 A / 60 V
ambient conditions	
ambient temperature	
<ul><li>during operation</li></ul>	-40 +60 °C
during storage	-40 +85 °C
during transport	-40 +85 °C
relative humidity	
at 25 °C / without condensation / during operation / maximum	95 %
protection class IP	IP20

SCALANCE PE408PoE

design, dimensions and weights	
design	SIMATIC S7-1500 device design
width	70 mm
height	147 mm
depth	125 mm
net weight	0.65 kg
fastening method	
19-inch installation	No
35 mm top hat DIN rail mounting	Yes
wall mounting	No
S7-300 rail mounting	Yes
S7-1500 rail mounting	Yes
product functions / management, configuration, engineering	
PROFINET conformity class	В
standards, specifications, approvals	
standard	
• for FM	FM3611: Class 1, Divison 2, Group A, B, C, D / T4, Class 1, Zone 2, Group IIC,
● IOI I IVI	T4
for safety / from CSA and UL	UL 508, UL 60950-1, CSA C22.2 Nr. 60950-1-03
for emitted interference	EN 61000-6-4 (Class A)
for interference immunity	EN 61000-6-2
reference code	
according to IEC 81346-2	KF
• according to IEC 81346-2:2019	KFE
standards, specifications, approvals / CE	
certificate of suitability / CE marking	Yes
standards, specifications, approvals / hazardous environments	
standard / for hazardous zone	EN 60079-0: 2009, EN60079-15: 2010, II 3 G Ex nA IIC T4 Gc, KEMA 07 ATEX
Standard / for flazardous zone	0145 X, IECEX DEK 14.0025X
• from CSA and UL	ISA 12.12.01-2012 (Hazardous Location), Class 1 / Division 2 / Group A, B, C,
	D / T4, Class 1 / Zone 2 / Group IIC / T4
certificate of suitability	
<ul> <li>CCC / for hazardous zone according to GB standard</li> </ul>	Yes
CCC / for hazardous zone according to GB standard / as	Ex nA IIC T4 Gc
marking	
standards, specifications, approvals / other	EN 04000 0 0 EN 04000 0 4
certificate of suitability	EN 61000-6-2, EN 61000-6-4
• C-Tick	Yes
KC approval	Yes
railway application in accordance with EN 50121-4	Yes
standards, specifications, approvals / marine classification	
Marine classification association	
<ul> <li>American Bureau of Shipping Europe Ltd. (ABS)</li> </ul>	Yes
<ul> <li>French marine classification society (BV)</li> </ul>	Yes
<ul> <li>Det Norske Veritas (DNV)</li> </ul>	No
Germanische Lloyd (GL)	No
• DNV GL	Yes
<ul> <li>Lloyds Register of Shipping (LRS)</li> </ul>	Yes
Nippon Kaiji Kyokai (NK)	Yes
<ul> <li>Polski Rejestr Statkow (PRS)</li> </ul>	Yes
Royal Institution of Naval Architects (RINA)	Yes
further information / internet links	
internet link	
• to web page: selection aid TIA Selection Tool	http://www.siemens.com/tia-selection-tool
to website: Industrial communication	http://www.siemens.com/simatic-net
to website: Industry Mall	https://mall.industry.siemens.com
to website: Information and Download Center	http://www.siemens.com/industry/infocenter
to website: Image database	http://automation.siemens.com/bilddb
to website: Image database     to website: CAx-Download-Manager	http://www.siemens.com/cax
<u> </u>	https://support.industry.siemens.com
<ul> <li>to website: Industry Online Support</li> </ul>	
to website: Industry Online Support security information	nttps://support.industry.siemens.com

security information

Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action(e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit http://www.siemens.com/industrialsecurity. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit http://support.automation.siemens.com. (V3.4)

last modified:

8/18/2023