

### product type designation



### W722-1 RJ45

IWLAN client, SCALANCE W722-1, RJ45, 1 radio, 1 R-SMA antenna port, iFeatures support IEEE 802.11a/b/g/h/n, 2.4/5GHz, gross data rate 150 Mbit/s, 1x RJ45 max. 100 Mbit/s, 24 V DC, joint block, IP20, 0... +55 °C, WPA2/802.11i/e, observe national approvals! CERT ID: ELN-W1-RJ-E1, scope of delivery: Manuals on CD-ROM, German/English, 1x joint block; for operation outside of USA/Israel .

### transfer rate

|   |                |
|---|----------------|
| transfer rate                           |                |
| • with WLAN / maximum                   | 150 Mbit/s     |
| • for Industrial Ethernet               | 10, 100 Mbit/s |
| transfer rate / for Industrial Ethernet |                |
| • minimum                               | 10 Mbit/s      |
| • maximum                               | 100 Mbit/s     |

### interfaces

|  |                       |
|--|-----------------------|
| number of electrical connections               |                       |
| • for network components or terminal equipment | 1                     |
| • for power supply                             | 1                     |
| • for redundant voltage supply                 | 0                     |
| type of electrical connection                  |                       |
| • for network components or terminal equipment | RJ45 socket           |
| • for power supply                             | 3-pole screw terminal |
| design of the removable storage                |                       |
| • C-PLUG                                       | No                    |
| • KEY-PLUG                                     | No                    |

### memory

|                                 |    |
|---------------------------------|----|
| design of the removable storage |    |
| • C-PLUG                        | No |
| • KEY-PLUG                      | No |

### interfaces / wireless

|  |                |
|--|----------------|
| number of radio cards / permanently installed                        | 1              |
| number of electrical connections / for external antenna(s)           | 1              |
| type of electrical connection / for external antenna(s)              | R-SMA (socket) |
| product feature / external antenna can be mounted directly on device | Yes            |

### supply voltage, current consumption, power loss

|   |        |
|---|--------|
| type of voltage / of the supply voltage | DC     |
| consumed current                        |        |
| • at DC / at 24 V / typical             | 0.15 A |
| power loss [W]                          |        |
| • at DC / at 24 V / typical             | 3.6 W  |
| supply voltage / 1                      |        |
| • from terminal block                   | 19.2 V |
| supply voltage / 2                      |        |
| • from terminal block                   | 28.8 V |

### ambient conditions

|                     |  |
|---------------------|--|
| ambient temperature |  |
|---------------------|--|

|  |   |
|--|---|
| <ul style="list-style-type: none"> <li>during operation</li> <li>during storage</li> <li>during transport</li> </ul> | 0 ... 55 °C   |
| relative humidity / at 25 °C / without condensation / during operation / maximum                                     | -40 ... +85 °C  |
| ambient condition / for operation  | -40 ... +85 °C  |
|  | 95 %  |
| protection class IP  | When used under hazardous conditions (Zone 2), the SCALANCE W761-1 RJ45 or W72x-1 RJ45 product must be installed in an enclosure. To comply with EN 50021, this enclosure must meet the requirements of at least IP 54 in compliance with EN 60529. |
|  | IP20  |
| <b>design, dimensions and weights</b>  |   |
| width  | 50 mm   |
| height   | 114 mm  |
| depth  | 74 mm   |
| width / of the enclosure / without antenna   | 50 mm   |
| height / of the enclosure / without antenna  | 114 mm  |
| depth / of the enclosure / without antenna   | 74 mm   |
| net weight   | 0.13 kg   |
| fastening method   |   |
| <ul style="list-style-type: none"> <li>S7-300 rail mounting</li> </ul>   | No  |
| <ul style="list-style-type: none"> <li>S7-1500 rail mounting</li> </ul>  | No  |
| <ul style="list-style-type: none"> <li>35 mm top hat DIN rail mounting</li> </ul>                                    | Yes   |
| <ul style="list-style-type: none"> <li>wall mounting</li> </ul>  | No  |
| <b>radio frequencies</b>   |   |
| operating frequency  |   |
| <ul style="list-style-type: none"> <li>for WLAN in 2.4 GHz frequency band</li> </ul>                                 | 2.41 ... 2.48 GHz; depending on the country approvals   |
| <ul style="list-style-type: none"> <li>for WLAN in 5 GHz frequency band</li> </ul>                                   | 4.9 ... 5.8 GHz; depending on the country approvals   |
| <b>product features, product functions, product components / general</b>   |   |
| product function / Access Point Mode   | No  |
| product function / client Mode   | Yes   |
| product function   |   |
| <ul style="list-style-type: none"> <li>iPCF client</li> </ul>  | Yes   |
| <ul style="list-style-type: none"> <li>iPCF-MC client</li> </ul>   | Yes   |
| number of iPCF-capable radio modules   | 1   |
| product function / iPRP  | Yes   |
| <b>product functions / management, configuration, engineering</b>  |   |
| number of manageable IP addresses / in client  | 4   |
| product function   |   |
| <ul style="list-style-type: none"> <li>CLI</li> </ul>  | Yes   |
| <ul style="list-style-type: none"> <li>web-based management</li> </ul>   | Yes   |
| <ul style="list-style-type: none"> <li>MIB support</li> </ul>  | Yes   |
| <ul style="list-style-type: none"> <li>TRAPs via email</li> </ul>  | Yes   |
| <ul style="list-style-type: none"> <li>configuration with STEP 7</li> </ul>  | Yes   |
| <ul style="list-style-type: none"> <li>configuration with STEP 7 in the TIA Portal</li> </ul>                        | Yes   |
| <ul style="list-style-type: none"> <li>WDS</li> </ul>  | No  |
| protocol / is supported  |   |
| <ul style="list-style-type: none"> <li>Address Resolution Protocol (ARP)</li> </ul>                                  | Yes   |
| <ul style="list-style-type: none"> <li>ICMP</li> </ul>   | Yes   |
| <ul style="list-style-type: none"> <li>Telnet</li> </ul>   | Yes   |
| <ul style="list-style-type: none"> <li>HTTP</li> </ul>   | Yes   |
| <ul style="list-style-type: none"> <li>HTTPS</li> </ul>  | Yes   |
| <ul style="list-style-type: none"> <li>TFTP</li> </ul>   | Yes   |
| <ul style="list-style-type: none"> <li>DCP</li> </ul>  | Yes   |
| <ul style="list-style-type: none"> <li>LLDP</li> </ul>   | No  |
| identification & maintenance function  |   |
| <ul style="list-style-type: none"> <li>I&amp;M0 - device-specific information</li> </ul>                             | Yes   |
| <ul style="list-style-type: none"> <li>I&amp;M1 – higher level designation/location designation</li> </ul>           | Yes   |
| <b>product functions / diagnostics</b>   |   |
| product function   |   |
| <ul style="list-style-type: none"> <li>PROFINET IO diagnosis</li> </ul>  | Yes   |
| <ul style="list-style-type: none"> <li>link check</li> </ul>   | No  |
| <ul style="list-style-type: none"> <li>connection monitoring IP-Alive</li> </ul>                                     | No  |
| <ul style="list-style-type: none"> <li>SysLog</li> </ul>   | Yes   |

|  |   |
|--|---|
| protocol / is supported  |   |
| • SNMP v1  | Yes   |
| • SNMP v2  | Yes   |
| • SNMP v3  | Yes   |
| <b>product functions / VLAN</b>  |   |
| product function   |   |
| • function VLAN with IWLAN   | No  |
| <b>product functions / DHCP</b>  |   |
| product function   |   |
| • DHCP client  | Yes   |
| • DHCP server  | Yes   |
| • DHCP Option 82   | Yes   |
| <b>product functions / redundancy</b>                                  |   |
| protocol / is supported  |   |
| • STP/RSTP   | Yes   |
| • MSTP   | Yes   |
| • RSTP   | Yes   |
| <b>product functions / security</b>                                    |   |
| product function   |   |
| • ACL - MAC-based  | Yes   |
| • management security, ACL-IP based                                    | Yes   |
| • IEEE 802.1x (radius)   | Yes   |
| • NAT/NAPT   | Yes   |
| • access protection according to IEEE802.11i                           | Yes   |
| • WPA/WPA2   | Yes   |
| • TKIP/AES   | Yes   |
| protocol / is supported  |   |
| • SSH  | Yes   |
| • RADIUS   | Yes   |
| <b>product functions / time</b>  |   |
| protocol / is supported  |   |
| • NTP  | Yes   |
| • SNTP   | Yes   |
| • SIMATIC time synchronization (SIMATIC Time)                          | Yes   |
| <b>standards, specifications, approvals</b>                            |   |
| standard   |   |
| • for FM   | FM 3611: Class I, Division 2, Groups A,B,C,D, T4 / Class 1, Zone 2, Group IIC, T4   |
| • for safety / from CSA and UL   | UL 60950-1, CSA C22.2 No. 60950-1   |
| certificate of suitability   |   |
| • EC Declaration of Conformity   | Yes   |
| • CE marking   | Yes   |
| • C-Tick   | Yes   |
| • E1 approval  | No  |
| • railway application in accordance with EN 50155                      | No  |
| • NEMA TS2   | No  |
| • IEC 61375  | No  |
| • IEC 61850-3  | No  |
| • NEMA4X   | No  |
| • Power-over-Ethernet according IEEE802.3at for type 1 and IEEE802.3af | No  |
| • Power-over-Ethernet according to IEEE802.3at for type 2              | No  |
| standard for wireless communication                                    |   |
| • IEEE 802.11a   | Yes   |
| • IEEE 802.11b   | Yes   |
| • IEEE 802.11e   | Yes   |
| • IEEE 802.11g   | Yes   |
| • IEEE 802.11h   | Yes   |
| • IEEE 802.11i   | Yes   |
| • IEEE 802.11n   | Yes   |
| wireless approval  | You will find the current list of countries at:<br><a href="http://www.siemens.de/funkzulassungen">www.siemens.de/funkzulassungen</a> |

#### standards, specifications, approvals / marine classification

|   |    |
|---|----|
| Marine classification association               |    |
| • American Bureau of Shipping Europe Ltd. (ABS) | No |
| • French marine classification society (BV)     | No |
| • DNV GL  | No |
| • Korean Register of Shipping (KRS)             | No |
| • Lloyds Register of Shipping (LRS)             | No |
| • Nippon Kaiji Kyokai (NK)                      | No |
| • Polski Rejestr Statkow (PRS)                  | No |
| • Royal Institution of Naval Architects (RINA)  | No |

#### standards, specifications, approvals / hazardous environments

|  |  |
|--|--|
| standard / for hazardous zone  | EN 60079-15:2005, EN 60079-0:2006, II 3 G Ex nA II T4 KEMA 07 ATEX 0145X |
| certificate of suitability / CCC / for hazardous zone according to GB standard | Yes  |

#### accessories

|             |  |
|-------------|--|
| accessories | 24 V DC screw terminal included in scope of delivery |
|-------------|--|

#### further information / internet-Links

|   |   |
|---|---|
| Internet-Link                                   |   |
| • to website: TIA Selection Tool                | <a href="http://www.siemens.com/tia-selection-tool">http://www.siemens.com/tia-selection-tool</a>   |
| • to web page: selection aid TIA Selection Tool | <a href="http://www.siemens.com/tia-selection-tool">http://www.siemens.com/tia-selection-tool</a>   |
| • to the website: IWLAN                         | <a href="http://www.siemens.com/iwlan">http://www.siemens.com/iwlan</a>                             |
| • to website: Industry Mall                     | <a href="https://mall.industry.siemens.com">https://mall.industry.siemens.com</a>                   |
| • to website: Information and Download Center   | <a href="http://www.siemens.com/industry/infocenter">http://www.siemens.com/industry/infocenter</a> |
| • to website: Image database                    | <a href="http://automation.siemens.com/bilddb">http://automation.siemens.com/bilddb</a>             |
| • to website: CAX-Download-Manager              | <a href="http://www.siemens.com/cax">http://www.siemens.com/cax</a>                                 |
| • to website: Industry Online Support           | <a href="https://support.industry.siemens.com">https://support.industry.siemens.com</a>             |

#### security information

|                      |   |
|----------------------|---|
| security information | Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action(e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit <a href="http://www.siemens.com/industrialsecurity">http://www.siemens.com/industrialsecurity</a> . To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit <a href="http://support.automation.siemens.com">http://support.automation.siemens.com</a> . (V3.4) |
|----------------------|---|

last modified:

7/1/2021 