

product type designation



W788-2 M12 EEC (USA)

IWLAN Access Point, SCALANCE W788-2 M12 EEC USA, 2 radios, 6 N-CON antenna port, iFeatures support via key plug, IEEE 802.11a/b/g/h/n, 2.4/5GHz, gross 450 Mbit/s per radio, 1x M12 max. 1 Gbit/s, PoE, redundant 24 V DC, M12 A-coded IP65, -40...+70 °C, plug slot WPA2/802.11i/e,conformal coating EN 50155, EN 45545, observe national approvals! CERT ID: RAPN-W2-M12-E3, includes: MPCIE-R1-ABGN-U3, scope of delivery: Manuals on CD-ROM, German/English, M12 sealing caps, only for operation in USA

transfer rate

transfer rate

- with WLAN / maximum
- for Industrial Ethernet

450 Mbit/s
10, 100, 1000 Mbit/s

transfer rate / for Industrial Ethernet

- minimum
- maximum

10 Mbit/s
1000 Mbit/s

interfaces

number of electrical connections

- for network components or terminal equipment
- for power supply
- for redundant voltage supply

1
1
1

type of electrical connection

- for network components or terminal equipment
- for power supply

M12 interface (8-pole, X-coded), PoE
M12 interface (4-pole, A-coded)

design of the removable storage

- C-PLUG
- KEY-PLUG

Yes
Yes

memory

design of the removable storage

- C-PLUG
- KEY-PLUG

Yes
Yes

interfaces / wireless

number of radio cards / permanently installed

2

transmission mode / for multiple input multiple output (MIMO)

3x3

number of spatial streams

3

number of electrical connections / for external antenna(s)

6

type of electrical connection / for external antenna(s)

N-Connect (socket)

product feature / external antenna can be mounted directly on device

Yes

supply voltage, current consumption, power loss

type of voltage / of the supply voltage

DC

supply voltage

- from Power-over-Ethernet according to IEEE802.3at for type 1 and IEEE802.3af
- from Power-over-Ethernet according to IEEE802.3at for type 2

48 V
50 V

consumed current

- at DC / at 24 V / typical

0.63 A

<ul style="list-style-type: none"> • with Power-over-Ethernet according to IEEE802.3at for type 1 and IEEE802.3af / typical • with Power-over-Ethernet according to IEEE802.3at for type 2 / typical 	0.22 A
power loss [W]	0.3 A
<ul style="list-style-type: none"> • at DC / at 24 V / typical • with Power-over-Ethernet according to IEEE802.3at for type 1 and IEEE802.3af / typical • with Power-over-Ethernet according to IEEE802.3at for type 2 / typical 	15 W
supply voltage / 1	10.7 W
<ul style="list-style-type: none"> • from M12 Power Connector (A-coded) for redundant power supply 	15 W
supply voltage / 2	19.2 V
<ul style="list-style-type: none"> • from M12 Power Connector (A-coded) for redundant power supply 	28.8 V
ambient conditions	
ambient temperature	
<ul style="list-style-type: none"> • during operation • during storage • during transport 	-30 ... +70 °C
relative humidity / at 25 °C / without condensation / during operation / maximum	-40 ... +85 °C
ambient condition / for operation	-40 ... +85 °C
	100 %
protection class IP	When used under hazardous conditions (Zone 2), the SCALANCE W788-x or W748-x product must be installed in an enclosure. To comply with EN 50021, this enclosure must meet the requirements of at least IP 54 in compliance with EN 60529.
design, dimensions and weights	
width / of the enclosure / without antenna	IP65
height / of the enclosure / without antenna	
depth / of the enclosure / without antenna	200 mm
net weight	176 mm
product feature / conformal coating	79 mm
fastening method	1.7 kg
<ul style="list-style-type: none"> • S7-300 rail mounting • S7-1500 rail mounting • 35 mm top hat DIN rail mounting • wall mounting 	Yes
	For 35 mm DIN rail mounting an additional mounting adapter is required
	Yes
	Yes
	Yes
	Yes
radio frequencies	
operating frequency	
<ul style="list-style-type: none"> • for WLAN in 2.4 GHz frequency band • for WLAN in 5 GHz frequency band 	2.41 ... 2.48 GHz; depending on the country approvals
	4.9 ... 5.8 GHz; depending on the country approvals
product features, product functions, product components / general	
product function / Access Point Mode	Yes
product function / client Mode	Yes
number of SSIDs	16
product function	
<ul style="list-style-type: none"> • iPCF Access Point • iPCF client 	Yes; Only in combination with the 'KEY-PLUG W780 iFeatures'
	Yes; Only in combination with the 'KEY-PLUG W780 iFeatures' or 'KEY-PLUG W740 iFeatures'
<ul style="list-style-type: none"> • iPCF-MC Access Point • iPCF-MC client 	Yes; Only in combination with the 'KEY-PLUG W780 iFeatures'
	Yes; Only in combination with 'KEY-PLUG W780 iFeatures' or 'KEY-PLUG W740 iFeatures'
number of iPCF-capable radio modules	0
product function / iREF	No; In combination only with 'KEY-PLUG W780 iFeatures'
number of iREF-capable radio modules	0
product function / iPRP	Yes; In combination with the 'KEY-PLUG W780 iFeatures' only
product functions / management, configuration, engineering	
number of manageable IP addresses / in client	8
product function	
<ul style="list-style-type: none"> • CLI • web-based management • MIB support • TRAPs via email 	Yes
	Yes
	Yes
	Yes

<ul style="list-style-type: none"> • configuration with STEP 7 • configuration with STEP 7 in the TIA Portal • operation with IWLAN controller • operation with Enterasys WLAN controller • forced roaming on IP down with IWLAN • forced roaming on link down with IWLAN • WDS 	Yes Yes No No Yes Yes Yes
protocol / is supported	
<ul style="list-style-type: none"> • Address Resolution Protocol (ARP) • ICMP • Telnet • HTTP • HTTPS • TFTP • DCP • LLDP 	Yes Yes Yes Yes Yes Yes Yes Yes
identification & maintenance function	
<ul style="list-style-type: none"> • I&M0 - device-specific information • I&M1 - higher level designation/location designation 	Yes Yes
product functions / diagnostics	
product function	
<ul style="list-style-type: none"> • PROFINET IO diagnosis • link check • connection monitoring IP-Alive • localization via Aeroscout • SysLog 	Yes No No Yes Yes
protocol / is supported	
<ul style="list-style-type: none"> • SNMP v1 • SNMP v2 • SNMP v3 	Yes Yes Yes
product functions / VLAN	
product function	
<ul style="list-style-type: none"> • function VLAN with IWLAN 	Yes
product functions / DHCP	
product function	
<ul style="list-style-type: none"> • DHCP client • DHCP server • DHCP Option 82 	Yes Yes Yes
product functions / redundancy	
protocol / is supported	
<ul style="list-style-type: none"> • STP/RSTP • MSTP • RSTP 	Yes Yes Yes
product functions / security	
product function	
<ul style="list-style-type: none"> • ACL - MAC-based • management security, ACL-IP based • IEEE 802.1x (radius) • NAT/NAPT • access protection according to IEEE802.11i • WPA/WPA2 • TKIP/AES 	Yes Yes Yes Yes Yes Yes Yes
protocol / is supported	
<ul style="list-style-type: none"> • SSH • RADIUS 	Yes Yes
product functions / time	
protocol / is supported	
<ul style="list-style-type: none"> • NTP • SNTP • SIMATIC time synchronization (SIMATIC Time) 	Yes Yes Yes
standards, specifications, approvals	
certificate of suitability	

<ul style="list-style-type: none"> • EC Declaration of Conformity • CE marking • C-Tick • E1 approval • railway application in accordance with EN 50155 • railway application in accordance with EN 50121-4 • fire protection in accordance with EN 45545-2 • NEMA TS2 • IEC 61375 • IEC 61850-3 • NEMA4X • Power-over-Ethernet according IEEE802.3at for type 1 and IEEE802.3af • Power-over-Ethernet according to IEEE802.3at for type 2 	<p>Yes</p> <p>Yes</p> <p>Yes</p> <p>Yes</p> <p>Yes</p> <p>Yes</p> <p>Yes</p> <p>Yes</p> <p>No</p> <p>No</p> <p>No</p> <p>Yes</p> <p>Yes</p>
standard for wireless communication	
<ul style="list-style-type: none"> • IEEE 802.11a • IEEE 802.11b • IEEE 802.11e • IEEE 802.11g • IEEE 802.11h • IEEE 802.11i • IEEE 802.11n 	<p>Yes</p> <p>Yes</p> <p>Yes</p> <p>Yes</p> <p>Yes</p> <p>Yes</p> <p>Yes</p>
wireless approval	For operation in the USA, you will find more information under: www.siemens.de/funkzulassungen

standards, specifications, approvals / marine classification

Marine classification association	
<ul style="list-style-type: none"> • American Bureau of Shipping Europe Ltd. (ABS) • French marine classification society (BV) • DNV GL • Korean Register of Shipping (KRS) • Lloyds Register of Shipping (LRS) • Nippon Kaiji Kyokai (NK) • Polski Rejestr Statkow (PRS) • Royal Institution of Naval Architects (RINA) 	<p>Yes</p> <p>Yes</p> <p>Yes</p> <p>Yes</p> <p>Yes</p> <p>Yes</p> <p>Yes</p> <p>Yes</p>

standards, specifications, approvals / hazardous environments

standard / for hazardous zone	EN 60079-15:2005, EN 60079-0:2006, II 3 G Ex nA II T4 KEMA 07 ATEX 0145X
certificate of suitability / CCC / for hazardous zone according to GB standard	Yes

further information / internet-Links

Internet-Link	
<ul style="list-style-type: none"> • to website: TIA Selection Tool • to web page: selection aid TIA Selection Tool • to the website: IWLAN • to website: Industry Mall • to website: Information and Download Center • to website: Image database • to website: CAX-Download-Manager • to website: Industry Online Support 	<p>http://www.siemens.com/tia-selection-tool</p> <p>http://www.siemens.com/tia-selection-tool</p> <p>http://www.siemens.com/iwlan</p> <p>https://mall.industry.siemens.com</p> <p>http://www.siemens.com/industry/infocenter</p> <p>http://automation.siemens.com/bilddb</p> <p>http://www.siemens.com/cax</p> <p>https://support.industry.siemens.com</p>

security information

security information	<p>Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action(e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit http://www.siemens.com/industrialsecurity. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit http://support.automation.siemens.com. (V3.4)</p>
----------------------	--

last modified:

12/15/2022 

